
IFC Reference Guide for ARCHICAD 25





Graphisoft®
Visit the Graphisoft website at <u>www.graphisoft.com</u> for local distributor and product availability information.
IFC Reference Guide for ARCHICAD 25
Copyright © 2021 by Graphisoft, all rights reserved. Reproduction, paraphrasing or translation without express prior written permission is strictly prohibited.
Trademarks
ARCHICAD® is a registered trademark of Graphisoft.
All other trademarks are the property of their respective holders.

Contents

Working with IFC	5
IFC File Types Supported by ARCHICAD	6
ARCHICAD Classifications and Categories in IFC	
Export IFC Model from ARCHICAD	9
Import IFC Model to ARCHICAD	12
Open IFC Model	14
Merge IFC Project	16
Hotlink IFC File	20
Update with IFC Model	24
IFC Project Manager	
Functions of the IFC Project Manager	
Navigating in the IFC Project Manager: Tree Structure	
Navigating in IFC Project Manager: Attributes and Properties	
Assign or Edit IFC Property/Attribute Values	
Create New, Custom IFC Property	40
Create New Classification Reference	43
Apply Predefined Rules	45
Using Assignments in IFC Project Manager	48
Using Type Products in IFC Project Manager	57
Manage IFC Data at Element Level	63
IFC Local Preferences	65
Define Element Criteria using IFC Data	66
IFC Translators: Overview	71
Translators for Import (Detailed Settings)	78
Model Filter for IFC Import	81
Type Mapping for IFC Import	83
Property Mapping for IFC Import	85
Using the Mapping Table	
Assigning Property Values in ARCHICAD (Based on IFC Property Mapping)	91
Geometry Conversion for IFC Import	96
Layer Conversion for IFC Import	
Material and Surface Conversion	103
Translators for Export (Detailed Settings)	106
Model Filter for IFC Export	110
Type Mapping for IFC Export	113
How to Fix Error Warnings in the Type Mapping Dialog	120
Geometry Conversion for IFC Export	127
Property Mapping for IFC Export	
How to create a Mapping Rule	139

Examples of Property Mapping Rules	142
Data Conversion for IFC Export	148
Unit Conversion for IFC Export	153
Filter Model at Import (Secondary Filter)	154
Filter Model at Export	157
Appendix: IFC Terms and Concepts	159
Model View Definitions	160
IFC Data Types	163
Appendix: IFC Data Mapping in ARCHICAD	171
Predefined Property Mapping (Export ARCHICAD to IFC)	172
Built-in IFC Type Mapping for ARCHICAD	177
Data Types for Properties in IEC and ARCHICAD	182

Working with IFC

IFC (Industry Foundation Classes) is an open, neutral data exchange format. It is optimized for OPEN BIMand model-based interoperability among disciplines, primarily in the AEC industry.

BIM, or "Building Information Modeling," is one of the biggest advances in the building industry's working methods since the introduction of CAD software. BIM is not synonymous with 3D projects. Three-dimensional geometric representation is only one part of the digital deliverables. A project includes non-graphical information, such as calculations, that are used in surveying, facility management and energy calculation. A prerequisite for a successful BIM project is that intelligent information can be exchanged between different software and even operating systems, throughout the stages of the building process. This interoperability demands a neutral file format with an open standard that supports different systems. IFC is such a system, enabling us to synchronize building models between the disciplines much more easily.

The IFC format is used for the efficient import and export of 3D elements and related non-geometric data, regardless of the application used to create the model. The IFC format is ISO-certified and can be integrated into any existing quality assurance polices your office may have. IFC is developed in part by buildingSMART (formerly the IAI - the International Alliance for Interoperability).

Graphisoft has played an active role within the buildingSMART organization since 1996 and supports the IFC standard. Through IFC, ARCHICAD can communicate with other disciplines within the context of the building model. The building model can be exported back to literally hundreds of other systems that support IFC.

The list of registered IFC supporter applications (by functional category/design disciplines) is available here.

ARCHICAD supports the import and export of both IFC2x3 and IFC4 versions. IFC data are managed according to the latest worldwide-certified IFC standard, IFC2x3 TC1 (Technical Corrigendum 1).

For more information, see the buildingSMART website.

This chapter provides an insight into the IFC standard and how it works in ARCHICAD.

Related Topics

IFC File Types Supported by ARCHICAD

ARCHICAD Classifications and Categories in IFC

Export IFC Model from ARCHICAD

Import IFC Model to ARCHICAD

Hotlink IFC File

Update with IFC Model

IFC Project Manager

Manage IFC Data at Element Level

IFC Local Preferences

Define Element Criteria using IFC Data

IFC Translators: Overview

Translators for Import (Detailed Settings)

Translators for Export (Detailed Settings)

Filter Model at Import (Secondary Filter)


Filter Model at Export

Appendix: IFC Terms and Concepts

Appendix: IFC Data Mapping in ARCHICAD

IFC File Types Supported by ARCHICAD

ARCHICAD supports the export and import of the following IFC data file formats:



- · .ifc: the default IFC exchange format using the STEP physical file structure
- .ifcXML: IFC data file using the XML document structure. This format is recommended for architects
 whose partners' applications cannot read the original .ifc format, but can manage XML databases (such
 as budget, energy calculations, etc.). This format delivers the same model information as the plain .ifc
 format, but the elements and their properties are stored in a more informative structure. An .ifcXML file is
 normally 300-400% larger than an .ifc file.
- .ifcZIP: IFC data file using the ZIP compression algorithm. It is the compressed version of .ifc or .ifcXML. An .ifcZIP file usually compresses an .ifc down by 60-80% and an .ifcXML file by 90-95%.

Note: .ifcZIP is compatible with e.g. Windows compressed folders, WinZip, etc. So if the recipient cannot read .ifcZIP, then a ZIP extractor application can open the file into .ifc or .ifcXML format.

ARCHICAD Classifications and Categories in IFC

Element Classifications for IFC
Structural Function Category for IFC
Position Category for IFC

Element Classifications for IFC


In ARCHICAD, you can optionally assign one or more classifications to any project element. A classification makes parameters and functions available to these elements for use by other applications: to organize project data, to make models transparent, to locate elements, for listing purposes, to share exact data, etc.

For each construction element, classifications can be set in the Classification and Properties panel of its Settings dialog box.

ARCHICAD provides a flexible way to classify elements according to any national or company standard classification system. You can assign one Classification value per Classification System in the Elements' Settings dialog, or from the Interactive Schedule.

Element classification affects the IFC export process: each element is saved to the IFC model according to an IFC Type.

This is displayed in the "IFC Type" item in the Classification and Properties panel (under IFC Properties).



Note: The IFC Type Mapping of ARCHICAD elements by classification depends on the Type Mapping for Export setting of the current Preview Translator. See <u>IFC Translators: Overview</u>.

Structural Function Category for IFC

"Load-Bearing Element" or "Non-Load-Bearing Element"

In collaborating with partners who are using structural programs, you can assign the "load-bearing" classification to elements in ARCHICAD and export this information with the IFC file.

Note: By default, Revit Structure will display only walls that have the "load-bearing" property in the "Structural" discipline views. But, if you forget to classify required walls as "Load-Bearing Elements" in ARCHICAD, the structural engineers can also change the bearing function of walls, or they can apply another display discipline (e.g. "Architectural") in order to show all walls exported from ARCHICAD. The current IFC standard supports the export of the "load-bearing" IFC property only for the following elements: Wall, Slab, Column, Beam, Roof; elements classified as such in ARCHICAD; and objects having these sub-types.

If you have classified ARCHICAD elements as "load-bearing", then you can use the Partial Structure Display "Core of Load-Bearing Elements Only" option to display those elements only. This is particularly useful if you wish to export only load-bearing elements to a structural engineer: in this case, just use the "visible elements" export mode on a view that uses this Partial Structure Display option.

This category is useful for listing purposes - for example, you can calculate the materials needed for all load-bearing walls or columns, separately from materials of non-load-bearing elements.

Criteria in the **Find & Select** dialog box include: search for those elements that have been defined as load-bearing or non-load-bearing, or whose Structural Function category is "Undefined". Since IFC export can be limited to selected elements only, you can - for example - export all selected elements defined load-bearing (not just their Core only, as described in the example above).

The load-bearing data is also a standard property of exported elements. Moreover, if other applications (such as a structural program) also categorize elements according to their load-bearing function, ARCHICAD can filter these elements upon importing them, and such elements will show up in the ARCHICAD model with that classification.

Position Category for IFC

"Interior" or "Exterior"

This category is useful if you plan to send an IFC file to partners (e.g. energy analyzers) who are able to differentiate elements by their location in the building. When you export the ARCHICAD model to IFC format, your model elements that are classified as "Interior" or "Exterior" will carry this information to the partner's application via IFC.

Naturally, the opposite is also true. Since Position (IsExternal) is a standard IFC property for certain building elements (e.g. Wall, Slab, Column, or Beam), if an imported IFC model contains such data, then the appropriate category is automatically added to the respective elements.

Criteria in the **Find & Select** dialog box include: search for elements categorized as either "Exterior" or "Interior", or whose position is "Undefined".

Interactive Schedule Criteria are also available to differentiate listed elements by Position.

Note: Within ARCHICAD, the Position category is fully usable as an ARCHICAD property (e.g. in **Find & Select** and **Interactive Schedule**). However, it will not be exported as an IFC property for certain element types (e.g. Ceiling (IfcCovering)) which are not supported by the IFC standard.

Export IFC Model from ARCHICAD

There are three export functions:

- Save as (File menu): exports the entire current ARCHICAD project or just its filtered content to an entirely new IFC file.
- Merge to IFC Model (File > Interoperability > IFC): merges only certain elements or, alternatively, the
 entire content of the current ARCHICAD project into an existing (unopened) IFC file. For example, use this
 command if you want to add selected content from an ARCHICAD model to an IFC file from another
 discipline.
- Publisher (Document menu): publishes views to any of the IFC file formats. For each Publisher item, you can vary the Translator, so that the view content can be customized to the needs of the recipient, creating the desired output with a single click.

Regardless of the method, the export process is controlled by an IFC Translator for Export, which defines how ARCHICAD elements should be interpreted and displayed in IFC. As part of the export process (see steps below), you will choose an IFC Translator for Export.

Save as IFC/Merge to IFC Model

Both of these export functions (Save as and Merge) follow essentially the same steps.

1. Choose the IFC export command you need.


File > Save as...

File > Interoperability > IFC > Merge to IFC Model

2. File type

Save as IFC: From the "Save as type" choose any of the IFC file formats.

Merge to IFC Model: Only the IFC file types are available.



Save as IFC

Merge to IFC Model

See IFC File Types Supported by ARCHICAD.


3. Define File Name

Use the "File name" field to define a file name (Save as), or browse for an existing IFC model (Merge to IFC Model).


4. Choose a Translator for Export

Use the drop-down list to choose among the predefined or user-defined translators.

See also <u>Translators for Export (Detailed Settings)</u>.



Click Options to open IFC Save Options, with a summary of the selected Translator settings.



5. Filter Model at Export

As needed, further filter the set of elements to export, using the **Elements to Export** dropdown and/or the Model Filter dialog box, both available from IFC Save Options.

See Filter Model at Export.

6. Export

Click "Save" (Save as) or "Open" (Merge to IFC Model) to start the export process.


Hint: After exporting an IFC model, it is good practice to check the IFC model in an IFC viewer (or in ARCHICAD by reopening the IFC file). There are many free IFC viewers on the market that can be readily downloaded, including:

DDS-CAD Viewer: http://www.dds-cad.net
 Solibri Model Viewer: http://www.solibri.com
 Tekla BIMsight: http://www.teklabimsight.com

Merge to IFC Model: Protected Content

In case of Merge to IFC Model, the content of the existing IFC file is protected: merging a file to IFC will only add to it, without replacing any of its elements. This means that if a merged element has the same IFC Globalld Attribute as an existing element in the IFC file, then the element will be merged using a new IFC Globalld Attribute. Elements will never be overwritten as a result of a merge. This also means that the Merge to IFC Model command is not suitable for merging changes from one version of an IFC file to another version of the same file!

This illustration shows the result of merging an ARCHICAD model into an existing file that contains an MEP model.



Import IFC Model to ARCHICAD

ARCHICAD provides three methods for importing an IFC model to ARCHICAD: Open, Merge, and Hotlink.

Open versus Merge

- Open: Opens the entire model or filtered parts of an IFC file as a new project. ARCHICAD will transform
 the imported elements into corresponding ARCHICAD elements, based on settings in the chosen IFC
 Translator for Import.
- Merge (File > Interoperability > Merge): Available only in Floor Plan view. Inserts an IFC model in whole or in part into a running ARCHICAD project. Merge preserves your running project, without overwriting its data (this is the "Reference model" concept). However, even in this "Reference model", the merged elements are real ARCHICAD elements based on the IFC-ARCHICAD mapping convention.
 In the Merge process, ARCHICAD automatically generates new IFC GlobalId (ARCHICAD IFC ID) values for all imported elements to avoid overwriting the IFC GlobalIDs of the host project. For the purposes of listing and searching, the elements' original GlobalId values are also retained, in the form of a parameter called "External IFC ID".

Overview of IFC Import: Defining how IFC Data are Converted to ARCHICAD

When you open (or merge or hotlink) an IFC file in ARCHICAD, the program carries out the following steps for each imported IFC element, using the settings in the chosen IFC **Translator for Import**:

- 1. Does the IFC element need to be imported to ARCHICAD? (based on the Translator's "Model Filter for IFC Import" preset
- 2. Which ARCHICAD tool (e.g. Wall, Object) should be used to place the IFC element in ARCHICAD? (This is based on the Translator's "Geometry Conversion for IFC Import" preset.)
- **3.** Which ARCHICAD layer should the element be placed on, and using which attributes? (This is based on the Translator's "Material and Surface Conversion for IFC Import" preset.)
- 4. Which ARCHICAD Classification should be assigned to the element? (This is based on the Translator's "Type Mapping for IFC Import" preset.)
- **5.** Based on the Classification: which Properties are available for the element? (This uses the Property Availability definitions, defined in the Classification Manager of the template file used at import.)
- **6.** Each of these Element Properties is populated with its default Property value. (This uses Property definitions of the Property Manager, in the template file used at import.)
- 7. The program examines the IFC data assigned to the incoming element, and attempts to generate the equivalent property value for the element in ARCHICAD (This is based on the Translator's "Property Mapping for IFC Import" preset.)

Important Note on Translators and Template Files

- When you import an IFC project using **Open** or **Hotlink IFC**: You will choose an IFC Translator for Import from an *external* Template file, selected by you.
- When you import an IFC project using the Merge command: You will choose an IFC Translator for Import from the current host project.

The following sections describe these processes.

Open IFC Model
Merge IFC Project

Hotlink IFC File

Related Topics:

IFC Translators: Overview

Translators for Import (Detailed Settings)

Filter Model at Import (Secondary Filter)

Open IFC Model Working with IFC


Open IFC Model

Follow these steps to import IFC data using the Open process.

- 1. Use File > Open.
- 2. Select the IFC File Format.
- 3. Choose the IFC file to import.
- 4. Use the drop-down list to choose among the IFC Translators.

Note: In the Open IFC process (just like the Place IFC Hotlink process), the file is imported based on an IFC Translator for Import, *from a Template file* selected by you.


For each listed Translator, its parent Template is shown in parentheses. If the Translator you need is not shown, you may need to search under a different template (see next step).



Open IFC Model Working with IFC

5. From the Open dialog, click Options to see IFC Open Options.

Here, each loaded template is shown together with its Translators, location, and presets. Choose a Translator from one of the templates and click OK, or click **Browse Template** to load another one.




6. Click "Open" to import the IFC model based on the selected Translator. Additional steps follow, depending on the type of imported model.

See Additional Options at IFC Import.


Merge IFC Project

- 1. Use File > Interoperability > Merge.
- 2. Select the IFC file format.
- 3. Choose the IFC file to merge.
- 4. Choose a Translator

Use the drop-down list to choose among the IFC Translators. These are the IFC Translators in the current host project.



5. Choose Info from the Merge dialog to see a summary of the selected Translator settings.



Note: In the Merge process, ARCHICAD uses an IFC Translator for Import that you choose *from the current host project*.

6. Click Open to merge the IFC Project to ARCHICAD.


7. Additional steps follow, depending on the type of imported model.

See next section.

Additional Options at IFC Import

Building and Site Selection

If the IFC file contains multiple IfcBuildings and/or IfcSites, then a Building Selection dialog appears, so you can select one Building. The import process can import only one building at a time.



On the left of this selection dialog, view the site and building hierarchy in the tree structure. At right, information is shown on each selected building.

If the "Import all Site geometry" checkbox (at the bottom left of the dialog box) is not enabled, then the selected IfcBuilding will be imported with only the geometry of the specific IfcSite to which the building is assigned.

To import the entire site model, regardless of the chosen building, activate the "Import all Site geometry" option.


Filter Model at Import

As needed, further filter the set of elements to import, using the Model Filter dialog box.

See Filter Model at Import (Secondary Filter).

Library Parts Location

Choose where to save Library Parts generated during IFC import:




The External location is recommended. Make sure you manually link this folder to the project as a Linked Library.

Notes:

- When updating a Hotlinked Module, the Linked Library will not be updated! If Linked Library contents
 have changed, you must update the library manually.
- Make sure that the target folder is write-enabled at the time of import. If it is not, the import process will fail.
- In Teamwork, the Linked Library option is not available; generated Library Parts are saved to the Embedded Library.

Position of Merged file



• Align merged file with either the Project Origin or Survey Point of the ARCHICAD model.


- · Match Stories:
 - Automatically: Stories are placed as they are in the incoming merged file.
 - Customize: Choose which story of the incoming IFC project which should be placed onto the current story in ARCHICAD. In the list, each story of the IFC model is shown with its own elevation in parentheses.

Note: In either case (**Automatic** or **Custom** stories), new stories will be created in the host project if needed, to accommodate extra stories in the merged project.

• **Elevation Offset:** To adjust the vertical position of the imported model, enter a positive or negative value in the Elevation Offset at the bottom of the dialog. By default (and this is recommended), the Elevation offset value is the absolute difference between the elevation values of the chosen IFC model story and the current ARCHICAD story.

Result

- The Result shows which merged stories will be placed on which stories of the host.
- New stories (if any) are marked with a plus sign. These stories will be created in the Host when you click OK to close the dialog box.



Hotlink IFC File

NOT AVAILABLE in ARCHICAD STAR(T) Edition 2022


NOT AVAILABLE in ARCHICAD 25 Solo

Place IFC files as hotlinks directly into the currently open Project as protected reference content. You can place this hotlink as many times as needed. Thus, in a project using repeated building blocks/parts, you do not need to request a huge IFC file based on the entire project - a smaller IFC file that contains just the module is enough.

Place IFC Hotlink

The steps for placing an IFC hotlink are the same as when placing a PLN-based hotlink, with some additional options described here.


- 1. As when placing any other Hotlink, use File > External Content > Place Hotlink.
- 2. From the New Hotlink Module dialog, choose an IFC format file and a Translator for Import.




Note: In the Place IFC Hotlink process (just like Open IFC), the hotlink elements are imported based on an IFC Translator for Import, *from a Template file selected by you*.

For each listed Translator, its parent Template is shown in parentheses. If the Translator you need is not shown, you may need to search under a different template (see next step).

3. From the Open dialog, click Options to see IFC Open Options.






Here, each loaded template is shown together with its Translators, location and presets. Choose a Translator from one of the templates and click OK, or click **Browse Template** to load another one.

See IFC Translators: Overview for more information.

4. Click **Select** to return to the **Place Hotlink** dialog box.

Note: When hotlinking an IFC file, make sure you set the Elements' Elevation option to Keep Elevation! Otherwise, the imported model may "fall apart" when its elements are placed in a different story structure



- 5. Click Place Hotlink.
- **6.** You are prompted to choose where to store the library parts.

See Library Parts Location.

7. If the IFC Translator for Import requires it, the **Model Filter for Import** also appears, to allow for further element filtering before placing the hotlink.

See Filter Model at Import (Secondary Filter).

Layers of IFC Hotlink Elements

When placing an IFC file as a Hotlink, remember that the imported elements' own Layers depend on the Layer Conversion settings of the Translator for Import that you are using.

See Layer Conversion for IFC Import.

Avoid Model Element Intersections with Hotlinked IFC Elements

Like other IFC content imported to ARCHICAD, IFC-based Hotlink content depends on the settings of the IFC Translator used for import.


If you are importing elements as native AC construction elements, unwanted intersections can be a problem.

To avoid intersections, do one of the following:

 Make sure the imported IFC elements are placed onto a separate ARCHICAD layer. (Check the Layer Conversion setting of the IFC Translator used for import.) (See <u>Layer Conversion for IFC Import.</u>)

Note: ARCHICAD will automatically apply a unique Layer Intersection Group setting to this new Layer. Elements whose layers have differing intersection numbers never intersect.

• Use the Translator's Geometry Conversion settings to create Objects or Morphs out of the imported elements. Such elements do not participate in automatic element intersections.



Watch the Video

Update with IFC Model Working with IFC

Update with IFC Model

This command (File > Interoperability > IFC > Update with IFC Model) updates the current ARCHICAD project content with an IFC model.


Use this if the ARCHICAD project and the IFC file contain elements in common, and if you want to add to or modify the project elements' data using IFC data.

- Exported ARCHICAD properties that are mapped to IFC properties are updated, provided that the correct Translator settings are used at both export and import. (ARCHICAD 22 and later)
- "Elements in common" are those whose Globalld Attribute is the same in both the host project and the imported IFC model.
- "IFC data" include IFC Attributes, IFC Properties and IFC Classification References

Thus, this command is optimized for tracking and updating changes to property data. This command is *not* suitable for updating model element changes.

Notes:

- Property update using this command works properly only if Property and Type Mapping definitions are used correctly and consistently, both at export and at import
- Deleted elements and modified elements are ignored!
- Geometry data (size, color, layer) will not be updated or modified.
- Properties of locked project elements will not be updated or modified.




Update with IFC Model Working with IFC

Workflow for Update

1. Go to File > Interoperability > IFC > Update with IFC Model.

In the Open dialog:



- Browse for an IFC model.
- Choose an appropriate Translator for Import. The Translator should use Property and Type Mapping settings that are analogous to those used when the original ARCHICAD model was exported to IFC.
- 2. Click Open.
- 3. In the appearing dialog, set the update options as needed (see *Update Options*, below).
- 4. Click OK.

Example Workflow: Property Mapping at Export and Import


- The ARCHICAD model is exported to IFC, using the File > Save As IFC command.
 ARCHICAD elements are exported together with their IFC data. Based on the Translator for Export Property Mapping for Export preset (which also depends on the Type Mapping for Export preset), ARCHICAD properties are mapped to IFC properties.
- 2. An external consultant works on the IFC model, deleting some properties, modifying others, and adding some new ones.
- The edited model is imported back to ARCHICAD using File > Interoperability > IFC > Update with IFC
 Model
- **4.** New and modified IFC properties are added and updated in the ARCHICAD model, based on the mapping definitions of the **Translator for Import Property Mapping for Import** preset.
- **Important:** To map the properties back to existing ARCHICAD properties, make sure you activate the option to **Import as ARCHICAD Properties.**

Update Options

Check the options to specify which data to update in the ARCHICAD model.

Note: These update data options are only relevant for incoming IFC Attributes and IFC Classification References. *Properties* are updated based on Translator-based property mapping definitions at export and import.

Update with IFC Model Working with IFC



- Merge new model elements from IFC
- **Merge new from IFC:** IFC Attributes and IFC Classification References which do not yet exist in the host project will be added to elements in common.
- Override existing if modified in IFC: For elements in common, the project data will be modified by the
 corresponding data values from the merged IFC file. Corresponding data: Attribute and Classification
 Reference must have the same name.


Note: This is a full override: all values for data items having the same name will be modified.

• Remove existing if missing in IFC: For elements in common, project data which do not exist in the merged IFC file will be removed.

IFC Project Manager

The IFC Project Manager (**File > Interoperability > IFC**) provides a hierarchical overview of the *current project's* IFC model database. Each model element is listed with its IFC attributes and properties.

Most of these are inherited from import/export IFC standards set elsewhere (e.g. Type Mapping and Property Mapping presets of the project's IFC Preview Translator.) However, you can edit values in IFC Project Manager for any specific element, and/or create custom IFC properties or Property sets as needed.



Related Topics:

Functions of the IFC Project Manager

Navigating in the IFC Project Manager: Tree Structure

Navigating in IFC Project Manager: Attributes and Properties

Assign or Edit IFC Property/Attribute Values

Create New, Custom IFC Property

Apply Predefined Rules

Using Assignments in IFC Project Manager

Using Type Products in IFC Project Manager

Functions of the IFC Project Manager


 View all IFC model entities generated from the ARCHICAD project (including IFC import content) in a hierarchy

- · View all IFC data available for project elements
- · Create new IFC data (custom IFC Properties and Classification Reference) for any model element
- Group elements or assign entities to elements (called IFC Assignments) and manage their IFC data
- Manage IFC Type Products assigned to elements with their with their IFC data
- Assign elements directly to the IfcSite or IfcBuilding. For example, the neighboring buildings and site
 context elements (trees, fences, roads, vehicles etc.) can be assigned to the IfcSite; thus, their default
 direct relation to their home story is removed.
- Update the IFC model with the modifications of the ARCHICAD project
- · Navigate easily between the ARCHICAD model and the IFC model
- Filter the IFC model by elements visible in the current view
- Find elements both in the IFC and ARCHICAD models by their IFC ID's
- In Teamwork, reserve the IFC Project Manager to modify data for the following elements: IfcProject, IfcBuilding, IfcSite, Assignments, and Type Products. To modify data for model elements (e.g. IfcWall, IfcColumn, IfcBeam) in IFC Project Manager, you must also reserve the elements themselves.

The IFC Project Manager palette is a modeless dialog box, so you can keep it open while working in the ARCHICAD project.

Navigating in the IFC Project Manager: Tree Structure

The tree structure (upper left side of the IFC Project Manager) displays the IFC model hierarchy and lists IFC Entities of the current project according to their "IFC Type" classification.




See IFC Model Hierarchy.

ARCHICAD Elements in IFC Story Structure

In ARCHICAD, all elements and objects are linked to their Home Story. Therefore, by default, elements are listed in the IFC model hierarchy under the IfcBuildingStorey that corresponds to their Home Story.

You can break this link (to the IfcBuildingStorey) by dragging the element out of its IfcBuildingStorey location into the IfcSite. For example, a neighboring building modeled with a Morph can be placed into the Site folder.




You can also place elements into the Building (such as an element that is logically tied directly to a particular building rather than a story).

To return an element to its automatic IfcBuildingStorey classification (corresponding to its Home Story), just drag it out of the IFC Project Manager.


Filter Data Shown in Tree

Click **List visible model elements only** to narrow the tree to those elements that are visible in the current ARCHICAD model view.




Synchronize Project Manager Data with Model

When elements are created or deleted in the ARCHICAD model, the tree will not register these changes automatically. If a refresh is needed, a message appears below ("Tree is not up-to-date!"). Click the "Synchronize" button to refresh it.



Find Selected Model Elements in Tree; Find Selected Tree Elements in Model




- To find and select IFC Entities of the tree in the ARCHICAD model, select them in the tree and click Show list selection in model. The program displays and selects the elements in the active window (Floor Plan or 3D view only).
- To find and select ARCHICAD model elements in the tree, select them in the Floor Plan or 3D window, and click **Show model selection in list**.

Find Tree Elements by IFC Identifiers

An IFC model checker might alert you to modeling errors. You can locate such elements in IFC Project Manager based on their IFC identifiers:


- ARCHICAD IFC ID (the Globalid IFC attribute automatically assigned by ARCHICAD to each element)
- External IFC ID (the Globalid IFC attribute assigned to each IFC element imported to ARCHICAD)

Switch to the search mode using the Find by Globalld tool (third icon underneath the tree).



Note: The External IFC ID is created when importing an IFC model to ARCHICAD using either Merge or Hotlink IFC. This is done to prevent existing ARCHICAD elements from being overwritten by identical elements being imported from IFC. (The External IFC ID stores the original ID of the model elements as defined in the external file).

Type the identifier (or any portion of it) that you are searching for into the empty field below the tool, and then click the "Search" button.



- Select any item in the "Search result" list to show that element in the tree.
- · Click "Show list selection in model" to find and select the element in the ARCHICAD model.


IFC Assignments View vs. IFC Type Products View

You can group IFC elements by Assignments and/or IFC Type Product.

See the descriptions of IFC Assignments and IFC Type Product.


To view these groupings in IFC Project Manager:

Switch to "Assignments" or "Type Products" view/definition mode using the first or second icon, respectively, underneath the tree.



View Items by Assignment or Type Product

To narrow the displayed Assignment/Type Product data to that of the selected elements only, click the "Filter for selected element(s)" button.




Related Topics

Using Assignments in IFC Project Manager
Using Type Products in IFC Project Manager

Navigating in IFC Project Manager: Attributes and Properties

Select a project element in the tree: for this selected item, the right side of IFC Project Manager displays:

- available IFC Attributes
- · Properties grouped in Property Sets
- · Classification References



In case of multi-selection, the IFC data of the last-selected element are shown.

At the top of the list, the numbers of selected/editable elements are shown.


Many IFC Property and Attribute are defined *automatically*, based on the Property Mapping rules defined in the IFC Translator for Export.

Filter Data Shown in IFC Project Manager

The predefined IFC data types are very numerous, and you usually don't need to see all of them at once in IFC Project Manager. Use the two filter buttons at top right to cut down on the data shown here:

Show only Properties from Active Preview Translator

Activate this button to display only those data based on to the Property Mapping preset of the Preview Translator.




Show only Properties from Active Preview Translator (Property Mapping for IFC Export)

See also Preview Translator and Property Mapping for IFC Export.

If you do not activate this filter, then IFC Project Manager also displays any new properties created here and in the Element Settings dialog boxes, as well as custom data added during an import process.

Show Only Items with Values


Use this toggle to display only those data which have assigned values: that is, its checkbox is enabled.



Note: A property whose field is empty, but whose checkbox is enabled, counts as a property that has a value assigned.

Assign or Edit IFC Property/Attribute Values

For any selected element in IFC Project Manager, overwrite any editable property or attribute value as needed.




The display of Attributes and IFC Properties in IFC Project Manager indicate the data status:

- BLACK: Editable items can be overwritten with a custom value.
- Checkbox: An active checkbox indicates that this property or attribute has a value.




Note: Don't forget that if you enable "Show only items with values", then items without a value are not shown here at all. See <u>Filter Data Shown in IFC Project Manager.</u>


RED ARROW: A customized value is shown with a red arrow: click it to revert to the original value.



- GREY: cannot be modified here in the IFC Project Manager.
 - The element's IFC Type depends on the Type Mapping definition of the Preview IFC Translator. This
 item is greyed and not editable here.
- Chained: This value is derived from some other interface. For example:



- The IsExternal and LoadBearing IFC properties (see image below) are greyed and not editable here.
 - These values depend on what is set in the ARCHICAD element's Settings dialog: the "LoadBearing" value comes from its Structural Function; and the "IsExternal" value comes from the Position.




• If a Property Set no longer contains any Properties, it will be deleted from the list automatically.

Create New, Custom IFC Property


IFC Properties are additional (mostly IFC Type-specific) parameters assigned to an IFC Entity. Standard, so-called "IFC2x3 Schema" data are defined by buildingSMART and stored in property sets whose names begin with the prefix "Pset_"

You may wish to create a custom Property or Property Set (e.g. an office-standard Property Set).

1. In IFC Project Manager, click New.



2. In the appearing dialog box, enter a new custom Property Set name (Pset); or else choose from the list of existing Property Set names defined previously for the same element type (click the arrow icon to access this list). For example, if you are creating a new Property for an IfcWall, the list contains all the Pset names earlier assigned to other IfcWalls.



Note: To avoid errors (and to keep the standard property definition rules), do not use the standard "Pset" prefix when giving a name to your custom Property Sets.

- 3. Enter a new Property name.
- 4. Choose a Property type (single, enumerated, complex, etc.) as described in the following table.

Property type	Definition		
Single Value	A property object which has a single (numeric or descriptive) value assigned.		
Enumerated Value	A property object whose value is chosen from an enumeration.		
Bounded Value	A property object which has a maximum of two (numeric or descriptive) values assigned, the first value specifying the upper limit and the second value specifying the lower limit		
Table Value	A property object which has two lists of (numeric or descriptive) values assigned, corresponding to a table with two columns.		
List Value	A property that has several (numeric or descriptive) values assigned, corresponding to an ordered list.		
Reference Value (IfcCalendarDate only)	A property object which references to calendar date-type entity (day, month, and year).		

5. Set the value type to label, text, integer, boolean, etc.

See also <u>Unit Conversion for IFC Export</u>

Value type	Definition		
IfcAreaMeasure	REAL type value of the extent of a surface. Value must be set in square meters, but is recalculated at export based on Area Unit settings.		
IfcBoolean	A defined data type of simple BOOLEAN type. Value: TRUE or FALSE.		
IfcIdentifier	An identifier is an alphanumeric STRING (max. 255 characters) which allows an individual thing to be identified. It may not provide natural-language meaning.		
lfcInteger	A defined data type of simple INTEGER type. The number of bits contained in the IfcInteger is unrestricted, but in practice it is implementation-specific.		
IfcLabel	A label is the term by which something may be referred to. It is a STRING (max. 255 characters) which represents the human-interpretable name of something and shall have a natural-language meaning.		
IfcLengthMeasure	REAL type value of a distance. Value must be set in meters, but is recalculated at export based on Length Unit settings.		
IfcLogical	A defined data type of simple LOGICAL type. Value: TRUE, FALSE or UNKNOWN.		
IfcMonetaryMeasure	REAL type value of an amount of money without regard to its currency. The currency unit can be set at Currency Unit settings.		
IfcPlaneAngleMeasure	REAL type value of an angle in a plane. Value must be set in radians, but is recalculated at export based on Angle Unit settings.		
IfcPositiveLengthMeasure	Length measure shall be greater than zero. Value must be set in meters, but is recalculated at export based on Length Unit settings.		

Value type	Definition	
IfcRatioMeasure	REAL type value of the relation between two physical quantities that are of the same kind. Input given in percent is expressed as a decimal value: e.g. 25% becomes 0.25.	
IfcReal	A defined data type of simple REAL type. The domain of Real is all rational, irrational and scientific real numbers. Here the precision is unconstrained, but in practice it is implementation-specific.	
IfcText	Alphanumeric STRING of characters which is intended to be read and understood by a human being. It is for information purposes only. No character number limitation.	
IfcTimeMeasure	REAL type value of the duration of time periods. The time unit can be set at Time Unit settings.	
IfcVolumeMeasure	REAL type value of the solid content of a body. Value must be set in cubic meters, but is recalculated at export based on Volume Unit settings.	
More Types	See the definitions at "alphabetical listing" > "Defined Types": http://www.buildingsmart-tech.org/ifc/IFC2x3/TC1/html/index.htm	

Note: All other "Measure"-type properties not listed in the above table are handled and exported without any unit settings.

- Newly created IFC data will appear in the defined Property Set or under "Classification References" in the IFC Project Manager, as well as in the element Settings dialog among the listed properties.
- Such newly created IFC data appear with a red X in front, meaning that you can delete them at any time.


Create New Classification Reference

A Classification Reference (IfcClassificationReference) arranges IFC elements into a category. You can assign an Item Reference identifier, a classification Name attribute and some other optional parameters to all project elements (such as the building, the stories, the building elements, or the zones).


You can classify elements with this system both in IFC Project Manager and the element Settings dialog.

Example


1. In IFC Project Manager, click New.



2. Click the Classification Reference button and assign it a new name. Here, too, you can choose from the list of existing Classification Reference names defined previously for the same element type (click the arrow icon to access this list).



• Assign values. The Classification Reference has 7 available items (the most important ones are the "Name" and the identifier ("ItemReference") of the classification reference data) for defining/editing.




To define values of a custom-defined Classification Reference data, type them manually or use the Apply Predefined Rule command:

See Apply Predefined Rules.

Apply Predefined Rules

Use this function to create custom-defined Classification Reference data based on automatic (.xml-based) rules.

1. In IFC Project Manager, click Apply Predefined Rule.



There are three types of predefined rules, based on their differing structures:

- "Tree list" rule: select an element from a tree-structure database to create the new data
- "Table" rule: select a row from a table to create the new data
- "Command" rule: start the rule-command to create the new data

The program contains factory-defined built-in rules (these vary depending on your localized version of ARCHICAD).


- The available rules are accessible from the following folder, and the newly created rules should also be saved to this location:
 - On Windows:
 GRAPHISOFT\ARCHICAD\Defaults\IFC Rules
 - On Mac:Applications\ARCHICAD\Defaults\IFC Rules

Apply Predefined Rule: Example


Assign classifications to a number of roof slabs (IfcSlabs) using the "OmniClass / Table 21 - Elements" rule:

In the model, select the Slab elements to be classified (you can use Find & Select). Open the Settings
dialog box and click on "Manage IFC Properties" from the Classification and Properties panel.
Alternatively, select the corresponding IfcSlab entities from the IFC Project Manager tree.

- Click on Apply Predefined Rule. From the dialog box, choose the "OmniClass / Table 21 Elements" rule.
- 3. In the database Search field, enter the text "roof", and click the search icon to execute the search. (This searches among the rules in the databases (tree list and table) based on any partial text.)
- 4. From the Search result area, select the "Roof Decks, Slabs, and Sheathing" title.



5. Click "Apply". The Classification Reference is generated, with the name of "Roof Decks, Slabs, and Sheathing", with an ItemReference value of "21-02 10 20 20", and additional data corresponding to the OmniClass standard.



Notes


- Once you select an element, only the applicable rules are available in the "Select Rule" list (for example, if
 you have selected IfcProject, then the "Concept Design BIM 2010 (US GSA) / Project Client/Owner and
 Project Architect" rule is available). All the non-applicable rules are grayed.
- IfcElement includes building, distribution (MEP) and furnishing elements.
- Certain rules are not available in Settings dialogs if the rules are related to elements which do not have Settings dialogs (for example, IfcBuilding, IfcBuildingStorey, IfcOccupant, IfcProject and IfcGroup).
- You can create and edit your own rule in .xml format. It is recommended to peruse the structure of an existing rule file (which may contain multiple rules), and to create a similar new rule by duplicating it under a different name.

Using Assignments in IFC Project Manager

Use IFC Assignments (IfcRelAssigns) to create groups of project elements. The major Assignment Types of the IFC4 standard can be seen in IFC Project Manager.

- IFC Groups
- IFC Zones
- IFC Systems
- IFC Building Systems
- IFC Distribution Systems

For more information on each Assignment type, see <u>IFC Assignments</u>.



Assignment Types in IFC Project Manager


To group IFC elements by IFC Assignment in IFC Project Manager:

- 1. Use the New button to create a new Assignment under an Assignment Type
- **2.** Drag relevant IFC entities from the top tree view into the newly created Assignment Relation item This process is described below.

Create New Assignment Relation


- 1. Switch to Assignment view mode by clicking the Assignments icon. (See illustration above).
- 2. Click on an Assignment type to select it (e.g. IFC Zones)

3. Click the "New" button at the bottom of the window.




As a result:

- A **New Assignment** (e.g. New Zone) is created for the selected Assignment Type.
 - A New Relation folder is created within the new Assignment. You can now add related IFC entities to this folder.
 - A New Spatial Relation node is also created within the new Assignment. (Not available for IFC Groups). You can add related spatial entities to this node.



4. Drag related items from the IFC Entity tree above into the New Relation folder and/or the Spatial Relation node.

Hint: Shift+click to multi-select, and grab the entities by their icons to drag them.



Click and Drag IFC Entity into New Relation Folder

See Examples of Assignments.

Which Entities Can Be Added?


Relation Folder: Entities that can be added to a Relation Folder depend on the Assignment type:

- IFC Groups: Drag any project elements here to create logical group(s)
- IFC Zones: Drag IfcSpace elements here
- IFC Systems: Drag IFC spatial types (IfcSite, IfcBuilding, IfcBuildingStorey and IfcSpace) and any of their related elements
- IFC Building Systems: Drag related building elements here. Possible items: IfcBuildingElement,
 IfcFurnishingElement, IfcElementAssembly, IfcTransportElement
- IFC Distribution Systems: Drag MEP elements (IfcDistributionElement and/or sub-elements) here.

Spatial Relation: Spatial IFC elements (Site, Building, Story, Zone) can be added to the Spatial Relation node.


Rename Assignment Item

Rename any newly created item using the Name Attribute field on the right side of the dialog.



Delete Assignment or Entity

To delete a Relation entity or Assignment, select it and click the "Delete" (red X) button.




Manage Assignment Hierarchy


- Within a particular Assignment Type, drag and drop entities among different Relation folders
- Define new hierarchies: Select an existing Assignment or Assignment Type item and click "New" to define a sub-item. This way, you can create a multi-level hierarchy within an Assignment Type.
- To copy an item, hold down Ctrl/Alt while dragging it
- To make a child Assignment into a parent Assignment, select it and drag it outside of the dialog box; it will reappear in the hierarchy as a parent Assignment

Examples of Assignments

• Create an IfcZone named "Security Zone", which will group together all of the project's IfcSpaces that have a security function.




• Group elevators in a vertical circulation system, which is a child system of a mechanical system.




MEP Modeler Elements: Automatic Assignment to IFC Distribution System

MEP Modeler elements can be automatically added to the **IFC Distribution System** Assignment, corresponding to each element's MEP System. For example:

1. At the IFC Distribution Systems Assignment Type: Click the New button to create a new, empty IFC Distribution System.




2. Select this new Distribution System, then click on the MEP icon at the right (underneath the Assignment list).



3. Choose the desired MEP System from the drop-down menu (e.g. Fresh Air). The Distribution System is renamed accordingly.

4. All elements that belong to this MEP System (e.g. Fresh Air) are automatically added from the tree into the "New Relation" folder.

Note: You can also add any other Distribution element manually to this folder.



To delete MEP System elements from an IFC Distribution System, select the Distribution System item (e.g. Fresh Air), and choose "Disconnected" from the drop-down menu of the MEP System options.

Using Type Products in IFC Project Manager

The IFC Project Manager displays all the IFC Type Products that exist in the project, plus all the elements which refer to them. IFC Type Products are another way to group project elements.


To see elements by Type Product, switch to the Type Products view/definition mode using the second icon underneath the tree.

Property Mapping rules can be defined for Type Products.


See an example here: Example 4: Mapping Rule by IFC Type Product.

An IFC Type Product defines a particular style/type of other entities by relating to them with common IFC Attributes and Properties. For example, IfcWindowStyle is an IFC Type Product, to which many windows (IfcWindow) refer.

IFC Type Product entities are generated for ARCHICAD elements based on the Type Mapping definition in the Translator for Export.



Select a Type (e.g. IfcWallType) to check its IFC data on the right side of the IFC Project Manager. The IFC data of the resulting IFC Type Product are not editable by default; they are displayed in italicized gray type, and all IFC data on the right side are grayed.




Edit IFC Type Product

You may wish to edit an IFC Type Product. For example:

- · Change its Name Attribute
- Define a value for an Attribute or standard Property that has no value yet
- Modify existing Property data
- · Create a new custom Property or Classification Reference

See Create New, Custom IFC Property.

To edit the IFC Type Product, first enable it for editing: click on the "Edit/New Type" button.



Then make the desired modifications in the attributes/properties on the right.


Change IFC Type Product Definition - Subtype

For some ARCHICAD elements, definition as a particular IFC Type Product is not always clear-cut - typically the case for HVAC elements (IfcDistributionElements).

Suppose you have an MEP Modeler-defined Pipe element, classified as IfcFlowSegment. The program will automatically choose a subtype of the IfcFlowSegmentType (e.g. IfcPipeSegmentType).

To change this to a different subtype of the IfcFlowSegmentType (such as IfcDuctSegmentType):

- 1. Make the IFC Type Product editable, using the "Edit/New Type" button.
- 2. Use the "Change Type Product" drop-down menu.




Combine IFC Type Products Into One

It is possible to combine several IFC Type Products entities into a single IFC Type Product. This works for all element types except Doors/Windows (see below).

For example, suppose you have two concrete Slabs of different thicknesses. By default, these will be classified as two separate IFC Type Products (IfcSlabType), because thickness is a significant property of slabs. But you want to combine them into a new, single type named "Concrete slabs."

- 1. Select one of the Type folders and make it editable using the "Edit/New Type" button.
- 2. From the other Type folder, select the IfcSlab drag it onto first Type folder.
- 3. Change the Name Attribute of the Type folder (which now contains two elements) to "Concrete slabs" (see illustration below).



Combine IFC Type Products of Doors and Windows


Combining doors or windows is more complicated, because some of their major parameters are generated from GDL data, and cannot be modified as a result of combining elements.

Such parameters are the OperationType Attribute and the panel and lining attributes. Suppose you have two doors that are identical in all their data (e.g. size, panel type), but their Operation Types are different: one opens to the right, the other to the left. These two doors will be classified under two different IFC Type Products: these two Types will have the same name, but their "OperationType" IFC Attributes will differ.

To have both doors belong to the same IFC Type Product, select one of the doors and place it in the other (second) type.


As a result, a new, common type is created that uses all of the data of the second type (such as Name Attribute, Properties, Classification Reference, etc.). This new common type is the one that will be exported, and which will be assigned to both of the doors. This common type can be renamed and its data modified.

At the same time, the two original types will remain as so-called linked types: they will link only data which is generated and which differ for each of the two doors (in this case, their OperationType Attributes). In other words, both doors will belong to a single type, which includes all of the data they have in common, but they will also maintain certain IFC data that were different for each and cannot be combined (see illustration below).




Reset Type

"Reset Type" means that all edited IFC data will revert to their original values, and the new data will be deleted.



- When Reset Type is applied to a selected IFC Type Product (e.g. IfcWallType) that has been edited, the Type's original data are restored (newly modified IFC data are lost), and the Type is no longer editable. If the Type now contains new elements as a result of combining Types, then those elements will return to their original locations.
- When Reset Type is applied to a single element (e.g. IfcWall) that has been moved into a different Type, that element will return to its original location.




Manage IFC Data at Element Level

ARCHICAD elements created from imported IFC model elements display their standard and custom IFC data, at the element level, in their respective Settings dialog boxes.

New IFC data can be added to the elements manually or automatically, based on predefined rules in the **Manage IFC Properties** dialog, which is opened from Element Settings (Classification and Properties panel). The interface of the Manage IFC Properties and all its functions are the same as the right side of the IFC Project Manager dialog box.

For detailed function descriptions, see IFC Project Manager.

The new data appear in the Classification and Properties panel of the element Settings dialog, under **IFC Properties**. Here, you can assign values to the available data fields that are still empty.




Working with IFC Data: Element Settings vs. IFC Project Manager

	Element Settings dialog	IFC Project Manager
management level	element-level only	project level
IFC data owner	building elements	building elements
	Zone (IfcSpace)	spatial elements:
		IfcProject
		IfcSite
		IfcBuilding
		Story (IfcBuildingStorey)
		Zone (IfcSpace)
		IFC Assignments
		IFC Type Products
		IFC Containers
Functions	collects and lists IFC data	collects and lists IFC data
	enables you to create,	enables you to create, edit and delete IFC data
	edit and delete IFC data	enables you to use predefined rules
	enables you to use	filters Mapping properties
	filters Mapping propertiesfilters only IFC data having values	filters only IFC data having values
		navigates between the ARCHICAD model and the
		IFC model
		displays Zone (IfcSpace) containment
		enables you to assign elements directly to the IfcSite or IfcBuilding

IFC Local Preferences Working with IFC

IFC Local Preferences

The settings defined at IFC Local Preferences (**File > Interoperability > IFC**) affect the way that IFC data are created and managed.



Save Library Parts Generated During Import To

Set the default location of imported Library Parts when opening or merging an IFC project.

See Library Parts Location.

Express Data Manager (EDM) path

The EDM (Express Data Manager) toolkit is the engine which creates an ARCHICAD model from the imported IFC model, and which also creates an IFC file out of the exported ARCHICAD model. The default engine is the recommended one, but you can use the Redefine option here to modify it as needed.

Define Element Criteria using IFC Data

Element criteria can include IFC data in the following functions:

- Find & Select
- Reserve Elements by Criteria (Teamwork)
- Interactive Schedule Schemes list IFC data assigned to current project elements

In these dialog boxes:

1. When defining element criteria, choose "IFC Properties" from the "Add" pop-up list.




2. The Select IFC Properties dialog box appears.

Select IFC Properties


All IFC data added to project elements are listed here.

You can narrow the displayed data:


- Include IFC properties from the Active Preview Translator (as opposed to those currently used in the Project). For example, you may want to define a Find & Select criteria set that includes properties (e.g. Fire Rating) which may not yet exist in your project;
- Find only the IFC data of a chosen IFC Type; and/or
- Search for IFC data by typing any text string in the "Filter" list field.



- 3. Select the IFC data item to use as element criteria. Click Add.
 - Multiselection is available
 - If you select a Property Set in the list, then all of the Properties it contains are added to the criteria.
 - If you select an Attributes folder or a Classification References folder, then all items contained in the folder are added to the criteria



4. Define operators and values for the criteria according to their type (label, integer, boolean etc.)
Note: In Find & Select: Get values for IFC data criteria from the model by applying the Pick Up Settings and Copy Settings tools to the owner element of the same IFC data type.)




Using IFC Properties in IES Schemes

- If you select a Property Set from the list, then all of the Properties it contains are added as fields.
- If you choose "IFC Assignment" as the parameter for Schedule Field, then the table will list (in non-editable form) all those IFC Assignments (their named branch) to which the element belongs. If an element has multiple Assignments, all of them will be listed, separated by a ";".
- If you list an element's "IFC Type Product" data, then the Schedule table will generate two columns: The "IFC Type Product Type" (e.g. 'IfcWallType') and "IFC Type Product Name") (the Name Attribute of the IFC Type Product).

Use IFC Data Types as Element Criteria


From the criteria or field selection interface (e.g. the Find & Select dialog):

- 1. Click the Add button.
- 2. From the appearing Properties list, choose an IFC Data Type:



- ARCHICAD IFC ID (the Globalid IFC attribute automatically assigned by ARCHICAD to each element)
- External IFC ID (the Globalid IFC attribute assigned to each element upon IFC import)

- IFC Assignment, e.g. IFC Group.
- IFC Type (see below)
- IFC Type Product, e.g. IfcColumnType.
- **3.** For IFC Type: the list is divided between all types available in the project (above the line) and all types that can be displayed and modeled in ARCHICAD (below the line).




The IFC Type list includes all so-called "parent" element type (these are collector entities that are above the other elements in the IFC entity hierarchy) - for example, IfcBuildingElement.

The following are examples of Find & Select possibilities using IFC data as criteria:

- 1. Find all elements that are members of any Assignment.
- 2. Find all elements of a particular IFC System.

3. Find all ARCHICAD Zones that have not yet been grouped into an IFC Zone.



Note: In Find and Select: the "Pick Up Settings" function does not work for IFC Assignment and IFC Type Product criteria.

IFC Translators: Overview Working with IFC

IFC Translators: Overview

Importing and exporting model data using IFC takes place according to the settings of the IFC Translator you are using. An IFC Translator defines the rules for which elements should be converted and how they should be interpreted - whether in ARCHICAD or in the external application reading the IFC file.

Basic Workflow for Using IFC Translators
Important Note on Translators and Template Files
IFC Translators Dialog Box - Overview
Preview Translator
Managing Translators

Basic Workflow for Using IFC Translators

ARCHICAD provides predefined, factory-default IFC Translators whose settings are optimized for the particular import/export purpose.

Most ARCHICAD users doing IFC export and import do not have to adjust any Translator settings. All you have to do is select a predefined translator from the Open dialog box (when importing a model in IFC format), or from the Save As/Merge to IFC dialog box (when exporting an ARCHICAD model to IFC format).

See Export IFC Model from ARCHICAD and Import IFC Model to ARCHICAD.


Important Note on Translators and Template Files

- When you import an IFC project using **Open** or **Hotlink IFC**: You will choose an IFC Translator for Import from an external Template file, selected by you.
- When you import an IFC project using the Merge command: You will choose an IFC Translator for Import from the current host project.

IFC Translators: Overview Working with IFC

IFC Translators Dialog Box - Overview

The **IFC Translators** dialog box (**File > Interoperability > IFC > IFC Translators**) allows you to view or modify Translator settings, or to create new Translators.



Translators are listed by name on the left side. The Translator name tells you what it is for: e.g. "Import from Modeling Applications" or "Export to Tekla Structures."

They are divided into **Translators for Import** and **Translators for Export**. The two groups of translators are not interchangeable, since they contain different settings.

- As needed, use the Search and Filter buttons at the top of the Translator list to locate a Translator.
 - The Filter button enables you to limit the list by IFC Schema: IFC2x3, or IFC4


See IFC Schema (Translators for Export only) for more information.

For complete details on all Translator settings, see the following sections:

Translators for Import (Detailed Settings)
Translators for Export (Detailed Settings)

Preview Translator

One of the Translators for Export is the Preview Translator, marked with the blue ARCHICAD icon:



The Preview Translator also provides default mapping definitions needed to work with IFC data in ARCHICAD. These essential mapping definitions are found in two presets of the Preview Translator:

Type Mapping for Export preset

The *Type Mapping preset* of the Preview Translator assigns an IFC Type to each exported ARCHICAD element. The IFC Type, in turn, affects which IFC properties are available to the element.

See also Type Mapping for IFC Export.

Property Mapping for Export preset (formerly IFC Scheme Settings)

Based on IFC Type, the *Property Mapping preset* of the Preview Translator provides the set of IFC Properties used for IFC data-related functions in ARCHICAD. For example, you can find/select/list IFC Properties in the following parts of the ARCHICAD interface:

- criteria in Find & Select
- criteria in Interactive Schedules
- Labels (e.g. Classification and Properties Label, ID and Properties Label)
- IFC Project Manager
- Element Settings (Classification and Properties panel)

All these interfaces use the Property Mapping that is set in the Preview Translator.

See also Property Mapping for IFC Export.

Use the Preview Translator:


- to export the model using the Properties visible in the current ARCHICAD model
- to see the IFC Properties in ARCHICAD as they are used in a particular IFC standard. For example, to
 work with the IFC Properties as defined by the COBie 2 Export standard for the US, go to the IFC
 Translators dialog box and switch the Preview Translator to "COBie 2 Export (US)".

Note: The Property Mapping preset contains Translator-specific settings. In ARCHICAD versions prior to 21, these settings were project-specific, and managed in IFC Scheme Setup.

For information on migrating legacy IFC Schemes, see the Migration Guide.


Set a Different Translator as the Preview Translator

- 1. Go to IFC Translators. (File > Interoperability > IFC)
- 2. Select a Translator for Export from the list.
- 3. Click Set Preview at the bottom of the dialog box.



Set Preview Translator

4. The selected Translator is now the Preview Translator, marked with the blue ARCHICAD icon:




Newly Defined Preview Translator

Managing Translators

Create New/Duplicate Translator

Do one of the following:

- · Click the New button at bottom left, or
- Click the Plus button at the right of the Translators group (Import or Export).



Delete Translator

Select a Translator, then click the **Delete** button at bottom left.

Multi-selection is not available.

• At least one Translator for Import and one Translator for Export must remain - you cannot delete the last one of either group.

Note: If you delete the Preview Translator, you are prompted to select a different Translator for Export to serve as the Preview Translator. (See also <u>Preview Translator</u>, below.)


Cancel Changes in IFC Translators

In the IFC Translators dialog box, clicking Cancel will discard all changes you have made not only to the main dialog box, but also in the sub-dialogs (the specific Conversion Preset settings dialogs.)

Import Translators From ARCHICAD Project

To import Translators from another ARCHICAD project:


1. Click the import button at bottom left.



2. Browse for the desired file type: PLN, PLA, or TPL

Note: You can no longer import IFC Translator files in XML format.

3. Click **Open**. In the appearing dialog, select one or more IFC Translators to import from the selected project.



4. Click **Import**. In case your project already contains Translators of the same name as the imported ones, you are prompted to choose how to manage these (Replace, Import with new file name, or skip.)

Importing Mapping Definitions

Certain IFC Translator Mapping definitions (Type Mapping for Import/Export, and Property Mapping) are also imported to your project if you use the **Import BIM Content** or **Download BIM Content** commands.

Watch the Video
Watch the Video

Translators for Import (Detailed Settings)


An IFC Translator for Import defines the rules for handling model elements when importing an IFC-based file to ARCHICAD.

For an overview of this topic, see <u>Overview of IFC Import: Defining how IFC Data are Converted to ARCHICAD</u>.

The **IFC Translators** dialog box (**File > Interoperability > IFC > IFC Translators**) allows you to view or modify Translator settings, or to create new Translators.


Select a Translator for Import from the list.

The selected Translator's settings, divided into six Conversion Presets, are shown on the right side.




Working with Conversion Presets

For any category of Conversion Preset, click the dropdown list to view or select a different Preset. The Preset name gives you an idea of how it will affect the imported IFC model, if this Preset is used in a given IFC Translator for Import.




Choose a different preset from this list if needed.

To adjust settings or create a new preset, select **Edit/Create New Preset**, or click the three buttons at the right of the Preset.



The Preset dialog opens (for example, the Geometry Conversion for IFC Import).



For each of the IFC Import Preset dialogs, view the following:

- Available Presets for this Conversion process (e.g. Geometry Conversion)
- **Settings** (this is where the import is defined in the greatest detail, for various data types, as defined for the currently selected preset at the top)
- Related Translators (all the currently defined IFC Translators for Import which use this Preset)

All Settings of each type of Conversion Preset (used by IFC Translators for Import) are detailed in the following sections.


Model Filter for IFC Import
Type Mapping for IFC Import
Property Mapping for IFC Import
Geometry Conversion for IFC Import
Layer Conversion for IFC Import
Material and Surface Conversion
Replace missing Renovation Status

Model Filter for IFC Import

File > Interoperability > IFC > IFC Translators

Choose a Translator for Import and open the Model Filter preset.

Show Model Filter on import



If this option is active, then - after you issue an Open or Merge IFC command - the Model Filter window will open.

This gives you the chance to overwrite, for the purposes of the current import process, the elements to be imported.

See Filter Model at Import (Secondary Filter).

Select 3D Elements to Import

By Structural Function

Use this as an additional (element-level) filter for import purposes, which takes into account the elements' "LoadBearing" IFC Property at import.

 "Load-Bearing elements only" means that only those elements whose IFC Property "LoadBearing Element" has a "True" value will be imported from the IFC file to ARCHICAD.


Notes:

- If no Structural Function classification has taken place in the ARCHICAD project, or if you have not finished the classifying process in ARCHICAD, then you should choose "All Elements" here: either of the other two settings ("Load-Bearing elements only" or "Non-Load-Bearing elements only") can result an empty IFC file, or one that is missing elements you might need.
- IfcPile and IfcFooting entities are load-bearing structural elements by definition, although they have no "LoadBearing" property in the IFC2x3 Schema. They are always handled as load-bearing elements at import.
- By IFC Domain

Use the IFC Domain to filter according to the following criteria for IFC import:

- "All" includes all elements from the model
- "Structural" includes only the structural building elements (IfcBuildingElement)
- "MEP" includes only the mechanical elements (IfcDistributionElement)

See the exact composition of each Domain filter in the tree list below. Modifying this filter will create a "Custom" filter.



Select 2D Elements to Import


- **IFC Grid:** During import, all IfcGrid elements of the IFC file will be imported and converted into grouped ARCHICAD Grid Elements.
- **IFC Annotations:** Check this to import all IfcAnnotation-type elements (including exploded dimension elements) of the IFC file into ARCHICAD. They will be converted into 2D elements (texts and lines).
- **IFC Door/Window Footprints:** During import, all generated doors and windows will be displayed in floor plan views with correct opening direction and sizes, based on their imported 2D symbols

Type Mapping for IFC Import

File > Interoperability > IFC > IFC Translators


Choose a Translator for Import and open the Type Mapping preset.

From this preset dialog, click Map IFC Types for Import to access the mapping definitions.



Use this chart to define how to classify IFC elements imported to ARCHICAD, based on their IFC Type.

At the top ("Target Classification System"), choose a Classification system in ARCHICAD whose definitions you want to use.



The IFC Type (far left column) is mapped to the Classification (far right column) as defined here. You can further narrow the mapping according to Predefined Types (if any) and User Defined Types.

"Any" means that the mapping does not take the Type definition into consideration when assigning the classification in ARCHICAD, even if the imported element has such a definition.


Watch the Video

Property Mapping for IFC Import

File > Interoperability > IFC > IFC Translators

Choose a Translator for Import and open the Property Mapping preset.

Use this Conversion Preset to define how to handle the properties of IFC elements imported to ARCHICAD.



Topics in this Section

Choose Import Method

Using the Mapping Table


Assigning Property Values in ARCHICAD (Based on IFC Property Mapping)

Importing IFC Data to ARCHICAD Categories

Replace missing Renovation Status


Choose Import Method

Choose either IFC Properties or ARCHICAD Properties:



Import as IFC Properties

- This is the default option: ARCHICAD imports all properties of the imported IFC elements.
- These data will now be available as IFC Properties in various parts of the ARCHICAD interface, such as Find & Select and Scheme Settings of element lists. (This is how IFC properties were imported in earlier AC versions.)
- If you choose this, you do not have to use Property Mapping.




Import as ARCHICAD Properties

This option can be useful if you wish to make certain IFC property data available for ARCHICAD functions which use ARCHICAD Properties (but not IFC Properties). These functions include:

- · Graphic Overrides
- Expression-defined Properties
- Collision Detection
- Autotext Labels

This option activates the mapping table. Use the table to define which IFC property values to import to which existing ARCHICAD Property.

- Each IFC Property in the list (defined using the first four columns from the left) is mapped to an ARCHICAD Property of the current project (far right column).
- No new ARCHICAD Properties are generated in the current project.
- · IFC properties not listed in this mapping table are ignored during import.




Remember:


- The set of ARCHICAD Properties available to any element in ARCHICAD depends on the element's Classification.
- Each ARCHICAD Property has a default value (assigned in Property Manager).
- For elements imported from IFC, this mapping table lets you change their ARCHICAD Property value from default to a custom value, based on the applicable IFC data if available.

Using the Mapping Table

- Each row represents a mapping rule. You can sort the rows by clicking the column headers.
- Click on any rule, then use the list item controls to set data types or to enter custom text.
 - In each rule, use the four IFC data columns Property, Property Set, Value Type, and Property Type to narrow the set of IFC data to be considered. (These are all IFC standard definitions.)



• To populate the table with the IFC properties of an existing file, click **Merge from IFC** and browse for an IFC file. The file's IFC properties and their data will be appended to the list as mapping rules.



• Use the New, Duplicate and Delete buttons to create and delete mapping rules.

For details and examples, see Assigning Property Values in ARCHICAD (Based on IFC Property Mapping)

Importing IFC Data to ARCHICAD Categories

The following ARCHICAD Categories always use the corresponding data from imported elements. (These are Categories, rather than ARCHICAD Properties.) This data is filled in automatically, without reference to IFC Translator settings.

Renovation Status


- · Structural Function
- Position



However, it is also possible to map these IFC values manually, in the mapping table, to any ARCHICAD Property.

Replace missing Renovation Status

Choose a Renovation Status in ARCHICAD (New, Existing or Demolished) for imported elements that do not have an assigned renovation status in IFC.



Notes:

 Nearly every model exchange scenario will lack automatic mapping of renovation status. The reason is that the IFC2x3 standard has no standard format for renovation status, and so the various applications will export this data only as custom IFC properties. In model exchange with Revit, the ARCHICAD "Renovation Status" item is mapped to Revit's
 "Phasing" item, provided that the IFC export and import on the Revit side is carried out using the <a href="https://exchange.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm.ncbi.nlm

Assigning Property Values in ARCHICAD (Based on IFC Property Mapping)

For general information on setting up the Property Mapping preset: see Property Mapping for IFC Import.

For each imported element, ARCHICAD attempts to execute the applicable mapping rules.

A mapping rule is applicable if the ARCHICAD Property is available to the element (based on its Classification).


The value of the mapped IFC property is assigned to the element's corresponding ARCHICAD Property. (It is a custom value.)

Example: Mapping Rule Applied

We have set up a mapping rule in the Property Mapping for Import preset of the current IFC Translator. According to this rule, the IFC property called Example_A is mapped to the ARCHICAD Property called Product Info A.




A Column, with an IFC data called "Example_A", is imported from an IFC file.



Element's Data in Source IFC File (as seen in Model Viewer)

The mapping rule is successfully applied: the Column element generated during import has a property called Product Info A, which is assigned a custom value (in ARCHICAD Element Settings, the Property value is displayed with the unlinked icon - it is no longer linked to its default value, set in Property Manager.)





Target ARCHICAD Property with Custom Value, after Element Import from IFC

Example: Non-Existent IFC Data

If a mapping rule refers to IFC property data that do not exist for the incoming element, then the element's ARCHICAD Property value becomes Undefined.


Two mapping rules are shown. One of them refers to an IFC data (Example_C) that does not exist for the element being imported.





Element's Data in Source IFC File (as seen in Model Viewer)

As a result, this mapping rule will assign the custom value of <Undefined> to the target ARCHICAD Property.



Target ARCHICAD Property with Custom < Undefined > value, after Element Import from IFC

Incompatible Data Types

If the mapped IFC element has a value, but it cannot be interpreted by the corresponding ARCHICAD
Property (e.g. incompatible data types): no custom Property value is assigned. The element uses the
ARCHICAD Property's default value.

Note on Data Types:

- IFC and ARCHICAD use different data type definitions: See <u>Data Types for Properties in IFC and ARCHICAD</u>. When you map an IFC Property to an ARCHICAD property, their data types do not necessarily have to coincide. ARCHICAD attempts to convert the data.
- If data conversion is not possible, the Session Report provides details on which elements' IFC data could not be converted.

Example


Two mapping rules are shown. One of these maps the "Example_A" IFC data (a string-type IfcLabel) to the Thermal Transmittance ARCHICAD Property, which is a String-type value. The mapping rule is successfully applied: the element generated during import shows a String-type custom value for the ARCHICAD Property of Thermal Transmittance.

The second mapping rule maps the "Example_A" IFC data to the Combustible ARCHICAD Property, which is a True/False type value. The data types do not match, so the mapping rule gets a Warning icon.



Mapping Rule to "Combustible" Property Referencing Incompatible Data Type

The targeted ARCHICAD Property does not get any custom value: it remains linked to its default value.



Property Mapping with Incompatible Data Types: No Change to ARCHICAD Property Value

• If no mapping rule applies to an element's given Property, then no custom Property value is assigned. The element uses the ARCHICAD Property's default value.


Conflicting Mapping Rules

The mapping table may include several IFC Properties mapped to the same single ARCHICAD Property. In this case, ARCHICAD will use the most specific rule. (The order in which the rules appear in the mapping table does not matter.)

In case of two or more equally specific mapping rules: the rules are ignored, and no mapping takes place.


A rule becomes more specific as its IFC data properties are more narrowly defined. (For example, IFC PropertySet data set to "Any" is less specific than if it is a defined IFC PropertySet.) Within a mapping rule, each field to the right further narrows its definition.

Here, two IFC data (Example_A and Example_C) are mapped to the same ARCHICAD Property. In this case, the more specific rule is automatically applied. Example_C is more specific, since it is narrowed down at the level of IFC PropertySet.



In the next example:

Several Thickness-related IFC Properties are mapped to a single Thickness Property in ARCHICAD. If an imported IFC element comes with multiple Thickness properties, then ARCHICAD has no way of determining which Property value to use in ARCHICAD. Thus, the rules are ignored for this imported element, and its ARCHICAD Property value remains the default one.




Geometry Conversion for IFC Import

File > Interoperability > IFC > IFC Translators

Choose a Translator for Import and open the Geometry Conversion preset.

Use this dialog box to define how to convert the geometry of IFC elements imported to ARCHICAD.



Building Elements

Convert to:

- Construction elements, otherwise Objects
- Construction elements, otherwise Morphs

With either of these options, IFC elements whose supertype is IfcBuilding (IfcWall, IfcColumn, IfcBeam, etc.) are imported as editable ARCHICAD elements ("Construction elements": Wall, Column, Beam, etc.) The advantage of converting the imported elements to AC tool-based construction elements is that they remain parametric, and ARCHICAD functions (such as automatic intersections) will apply to them. Even if you choose the "Construction element" option, some elements cannot be imported in this form: such as non-extruded (BREP geometry) elements, or elements having no counterpart in ARCHICAD).

For such elements, you can choose to convert them as either an editable Morph or an Object ("otherwise Objects/otherwise Morphs").

- Morphs
- Objects

- Conversion of elements to Morphs or Objects guarantees perfect geometry import.
- The resulting Morphs will be editable.
- The resulting Objects will be Library Parts, whose subtype will match the IFC entity type: for example, an IfcColumn converted to an ARCHICAD Object will have the subtype "Column".

Distribution elements

This option applies to imported elements whose domain is MEP (IfcDistributionElement).

These elements can be converted to one of three results:

- Morphs
- Objects
 - Conversion of elements to Morphs or Objects guarantees perfect geometry import.
 - The resulting Morphs will be editable.
 - The resulting Objects will be Library Parts, whose subtype will match the IFC entity type: for example, an IfcColumn converted to an ARCHICAD Object will have the subtype "Column".
- MEP Elements: this option generates parametric MEP elements from the project's MEP elements. Even if
 you choose this option, the MEP IFC model might not contain sufficient data to generate the parameters,
 in which case non-parametric MEP Equipment elements will be generated, or in case of limited data Objects will be generated.

Other elements

This option defines how to convert elements that are neither building elements nor distribution elements (such as furnishing and transportation elements).

- Morphs
- Objects
 - Conversion of elements to Morphs or Objects guarantees perfect geometry import.
 - The resulting Morphs will be editable.
 - The resulting Objects will be Library Parts, whose subtype will match the IFC entity type: for example,
 an IfcColumn converted to an ARCHICAD Object will have the subtype "Column".

IFC Site geometry

Check this box if you want to include the geometry of the imported IfcSite.

Define whether the converted element should be an editable Morph or an Object. (IfcSite geometry cannot be converted to an ARCHICAD Mesh.)

Define how to position the imported IFC model

Match ARCHICAD Project Origin with:

- IFC Site Location (Recommended)
- IFC Global Origin

Import Unnamed IFC Profiles

Choose how to handle unnamed IFC profiles imported to ARCHICAD:

Custom Profiles (this option does not create any new attributes in the ARCHICAD project)

• Profile Attributes (new Profile attributes are added to the ARCHICAD project)

Notes on Geometry Conversion


- To optimize the management of shared geometry, ARCHICAD creates as few geometric elements (when generating Morphs) or as few Library Parts (when generating Objects) as possible.
- Objects can be placed in the project's Embedded Library, or else saved to a given linked library (see <u>IFC</u>
 <u>Local Preferences</u>).
- Some IFC models may contain elements with special geometry which cannot be converted to Morphs, even if you choose the Morph conversion option. In this case, ARCHICAD will generate Objects, to achieve perfect geometry import.
- Imported IfcSpace elements will always be generated as ARCHICAD Zones, which will always retain the imported elements' original geometry.

Layer Conversion for IFC Import

File > Interoperability > IFC > IFC Translators

Choose a Translator for Import and open the Layer Conversion preset.

Use this dialog to define the method for placing the imported elements onto ARCHICAD layers. You can choose between three different methods:



Place all elements on a single new Layer

Imported elements will be placed onto a newly created, single layer that you define (such as the "IFC Import" layer). (Enter the desired text in the input field.) Original layer names of the IFC model will be lost.


Create new Layers to keep original Layer structure

ARCHICAD will create layers using the original layer names (e.g. IfcPresentationLayerAssignment) of the IFC model, and will place the imported elements onto these layers.

• Extend original Layer names with suffix: Check this to add a custom extension (such as "IFC Model") to each Layer name. (Enter the desired text in the input field). The advantage is that you will be able to sort the layers by extension in ARCHICAD's Layer Settings dialog box.


Use existing ARCHICAD Layers

From the Default Layer popup, choose an existing layer from the ARCHICAD project on which to place imported elements.



Override default Layer with mapping

Check this box to map individual layers manually, instead of using the default Layer assigned from the pop-up.




Click **Merge from IFC** to browse for the IFC model and append its IFC Layer names to the list in the Mapping dialog.

Alternatively, click **New** to add an IFC Layer name manually.

Assign Layer to SEO Operators Used to Generate Openings

Some imported openings can be created in ARCHICAD only by using Solid Element Operations. In such cases, ARCHICAD uses operator elements to generate the openings automatically via SEO.

At IFC import, you can define the layer settings of these SEO operator elements:



- · Create new dedicated Layer
- Use existing ARCHICAD Layer

Note: If you move any of the target elements, make sure that the operator elements' layer is shown, and move the target and operator elements together: do this to avoid modifying the original geometry of the imported elements.

Notes on Layer Conversion:


- The import process automatically sets an intersection group number for all imported layers, and this
 number will be different from the current project layers' intersection group number. This difference ensures
 that the elements on the imported layers will not intersect with the existing project elements.
- If the elements have been converted to their counterpart ARCHICAD tool-based construction elements (that is, they have not been converted to Objects or Morphs; see <u>Geometry Conversion for IFC Import above</u>), then elements on identical layers might have their geometries modified due to automatic intersections. If you want to avoid this, set the intersection group number to 0.
- If layers of the same name already exist in ARCHICAD, no new layers are created; the imported elements are placed onto the corresponding, existing ARCHICAD layers.

Material and Surface Conversion

File > Interoperability > IFC > IFC Translators

Choose a Translator for Import and open the Material and Surface Conversion preset.

Use this dialog to choose how to assign ARCHICAD Building Materials to imported IFC model elements.



There are two import methods:

Method 1: Replace IFC Materials with existing ARCHICAD Building Materials

With this method, a single ARCHICAD Building Material is assigned to all imported IFC elements. Choose this default Building Material from the pop-up below. No new Building Materials are generated.

If needed, you can override this default definition by using Material Mapping: see <u>Override default Material</u> <u>with mapping</u>, below.

Method 2: Create ARCHICAD Attributes from IFC Materials

For each IFC Material, a new ARCHICAD Building Material will be created: the default Building material chosen below will be duplicated.


The new Building material:

is named using the IFC Material's Name parameter

· is assigned a color corresponding to the IFC Material Color parameter

Override default Material with mapping

Check this box to map individual materials manually, instead of using the default Building Material assigned from the pop-up.



Click **Merge from IFC** to browse for the IFC model and append its IFC Material names to the list in the Mapping dialog.

Alternatively, click New to add an IFC Material name manually.

Note:


- Some of the default IFC Translators for Import include predefined mapping rules, whose settings you
 are free to expand or edit. It is recommended to duplicate the default translator before modifying it.
- You cannot import or export these mapping tables as separate files (e.g. xml); you must import/export them together with entire translator file itself.

Override Material colors with IFC element geometry surfaces

IFC elements in IFC models can have two colors: a material color and an additional color for the surface geometry color.

If you check this **Override Material colors** box, ARCHICAD will create Surface attributes using the color assigned to the IFC element's surface geometry.

To check and modify the resulting surface overrides in ARCHICAD, view the Model panel of the respective Element Settings dialog box.



Translators for Export (Detailed Settings)

An IFC Translator for Export defines the rules for handling model elements exported from ARCHICAD to an IFC format.

For an overview of this topic, see IFC Translators: Overview.

The **IFC Translators** dialog box (**File > Interoperability > IFC > IFC Translators**) allows you to view or modify Translator settings, or to create new Translators.


Select a Translator for Export from the list.

The selected Translator's settings, divided into six Conversion Presets, are shown on the right side.

One of the Translators for Export is the **Preview Translator**. The Preview Translator exists to provide default mapping definitions needed to work with IFC data in ARCHICAD.

For details, see Preview Translator.

The **IFC Schema** and **Model View Definition** categories help in setting up presets that are compatible with particular standards (see details below).



IFC Schema (Translators for Export only)

An IFC Schema is a particular version of the IFC standard. ARCHICAD Translators can support either Schema IFC2x3 (recommended) or IFC4.

Note: IFC2x3 is recommended - this is the most widely used version. Choose IFC4 only if you are certain that it is supported by the application that will receive IFC data using this Translator.


Model View Definition (Translators for Export only)

A *Model View Definition* (MVD) is a recommendation for which data and elements the IFC model should include, depending on the purpose of the model exchange. If your exported IFC model must conform to a predefined standard MVD, choose that MVD from the list.

Note: Available MVD's depend upon the IFC Schema chosen above: IFC2x3 or IFC4.


For a more detailed explanation of MVD's and their characteristics, see Model View Definitions.

Once you choose an MVD, then certain Translator for Export settings must conform to the requirements of that MVD. If you change a Translator setting so that it no longer conforms to the selected MVD's requirements, then the Translator becomes invalid, and you get a warning in the dialog box. The problematic setting is also marked:




Working with Conversion Presets


For any category of Conversion Preset, click the dropdown list to view or select a different Preset. The Preset name gives you an idea of how it will affect the exported IFC model, if this Preset is used in a given IFC Translator for Export.



To adjust settings or create a new preset, select **Edit/Create New Preset**, or click the three buttons at the right of the Preset.



The Preset dialog opens (for example, the Geometry Conversion for IFC Export).




For each of the IFC Export Preset dialogs, view the following:

- Available Presets for this Conversion process (e.g. Geometry Conversion)
- **Settings** (this is where the export is defined in the greatest detail, for various data types, as defined for the currently selected preset at the top)

 Compatibility: Feedback on whether the current settings of this preset conform to particular Model View Definitions.

Click the **Info** button to see the settings conflicts, if any. (If the current Translator for Export does not use that particular MVD, then this conflict need not be a problem.) To ensure compatibility with the MVD, you can adjust the settings as shown in the Info dialog, or just click the **Override Settings** button to solve the issue.



Related Translators (all the currently defined IFC Translators for Export which use this Preset)


All Settings of each type of Conversion Preset (used by IFC Translators for Export) are detailed in the following sections.

Model Filter for IFC Export
Type Mapping for IFC Export
Geometry Conversion for IFC Export
Property Mapping for IFC Export
Data Conversion for IFC Export
Unit Conversion for IFC Export

Model Filter for IFC Export

File > Interoperability > IFC > IFC Translators

Choose a Translator for Export and open the Model Filter preset.



Select 3D Elements to Export

This filter defines which ARCHICAD 3D elements should be exported to IFC. You can filter by the elements' Structural Function and/or by their IFC Domain.

By Structural Function

This is an additional filter to the IFC Domain filter set below.


- This filter considers the ARCHICAD element's "Structural Function" category: Either Load-Bearing
 or Non-Load Bearing. This is set for each element in its Classification and Properties panel of
 Element Settings.
- "Load-Bearing elements only" means that only those elements classified as "Load-Bearing Element" (plus ARCHICAD Zones) will be exported from ARCHICAD to IFC.
- By IFC Domain

Note: An element's IFC Domain depends on its Type Mapping preset.

"All" includes all elements from the model

- "Structural" includes only the structural building elements
- "MEP" includes only the mechanical elements (IfcDistributionElement).

See the exact composition of each Domain filter in the tree list below. Modifying this filter will create a "Custom" filter.



Select 2D Elements to Export

 Grid System and Elements: Check this to include the Grid Elements and the grid members of Grid Systems in the exported file.

Grid elements will show up in the IFC structure as IfcGrid.

- Lines, Texts, Labels, Fills: Check this to export these 2D elements, plus all dimension types.
 - 2D elements will show up in the IFC structure as IfcAnnotation.
 - Dimensions will be exploded into lines and texts, since the IFC2x3 standard documentation does not include a dimension element.
 - The inclusion of 2D elements in the exported file is also affected by the "Elements to Export" filter at
 "IFC Save Options": if a 3D view is currently active, the 2D elements can be included only if the "Entire
 project" option is selected in that filter. (See <u>Filter Model at Export</u>.)
 - IFC4 Reference View does not allow annotations. To ensure compatibility for IFC4 Reference View, leave this box unchecked.


• **Door/Window 2D Views:** Check this box to include the 2D symbols of doors and windows in the export process, in addition to 3D model geometry. This is handy if the recipient program recognizes these data and can correctly display, for example, the door opening directions.

Type Mapping for IFC Export

File > Interoperability > IFC > IFC Translators

Choose a Translator for Export and open the Type Mapping preset.

From this preset dialog, click the Map IFC Types for Export to access the mapping definitions.



Topics in this Section

About Type Mapping for Export Mapping by Element Type Mapping by Classification

Watch the Video

About Type Mapping for Export

When a model is exported to IFC format, every one of its elements is assigned an IFC Type.

This dialog defines how to assigns an IFC Type to each exported ARCHICAD element.

There are two ways to take care of Type Mapping for IFC Export:


- By Element Type
- By Classification

Each is described below.

Mapping by Element Type

Assigns each ARCHICAD Element Type automatically to a default, basic IFC Type, corresponding to its ARCHICAD tool or (for GDL objects) to its Object Subtype.

If you choose this method, no further manual mapping is needed. The rest of the dialog controls are inactive.




For more details, see Built-in IFC Type Mapping for ARCHICAD.

Mapping by Classification

Maps each ARCHICAD Classification to an IFC Type, Type Product, and/or Predefined Type. This method allows for flexible and detailed IFC Type classification, according to specific IFC standards.

To use this method:

1. Select Mapping by Classification.




- 2. Choose a **Classification System** (among those available in the ARCHICAD project). The Classifications of the selected System are now listed on the left side of the dialog.
- 3. Set the Filter to display IFC Type definitions by the IFC4 Schema, the IFC2x3 Schema, or both. This is relevant for fixing erroneous mapping definitions (see <u>How to Fix Error Warnings in the Type Mapping Dialog</u>). By default, the filter automatically corresponding to the IFC Schema of the current preset.

Now you can map the Classifications on the left to the IFC Type definitions on the right, as detailed below (By Parent and Custom).

Classification Mapping by Parent


For a selected Classification (e.g. Pilaster): "By Parent" maps it to the same IFC Type as its parent item (e.g. Pilaster gets the same IFC Type as Column, that is: "IfcColumn"). Classifications mapped "by Parent" are shown in blue: you don't have to define its IFC Type, because it will automatically get the same one as its parent.



Custom Classification Mapping

Maps the Classification to an **IFC Type** and **IFC Type Product** selected by you. This assigns more specific IFC Type definitions to the exported elements.


For example, here an element is classified in ARCHICAD as Thermometer, and it is mapped to the IFC Type and IFC Type Product assignments as shown: just click the popups to access a list of valid definitions.



Map to IFC Type and IFC Type Product

If the chosen IFC Type or IFC Type Product have Predefined Types, you can map those too.

Here, the Flow element's Type Product is assigned the Predefined Type of PRESSUREGAUGE:




Choose a Predefined Type

User Defined Type

If the list of Predefined Types does not contain what you need, choose USERDEFINED and then enter the desired value in the text field below.


Synchronize Predefined Type Values

In most cases, the Predefined Types for IFC Type and IFC Type Product should be identical. To speed things up, the **Synchronize** checkbox is on by default:



Invalid Predefined Types

If a Classification element is mapped with a Predefined Type that is not available in the current Schema (e.g. the MOLDING value is available in IFC4 but not IFC2x3), then this value will be grayed out, and will not be exported. (The Translator preset will still be valid.)



Reset Mapping

Click this button to undo the mapping definitions made since opening the dialog.

Note: The Type Mapping preset of the *Preview Translator* has an additional function: to define the default IFC Type classification of elements in the current ARCHICAD project.

See also Preview Translator.

Related Topics

IFC Type


How to Fix Error Warnings in the Type Mapping Dialog


Watch the Video

How to Fix Error Warnings in the Type Mapping Dialog

ARCHICAD includes two Presets for Type Mapping for IFC Export. Each Preset is optimized for a supported IFC Schema: IFC2x3 or IFC4.

If you use the predefined Presets, as shown in the images below, the mapping will be correct.






Type Mapping Preset for IFC2x3 Schema

Type Mapping Preset for IFC4 Schema


If you *customize* the Type Mapping preset or change the Schema definition, this may result in mapping definitions that are obsolete or incorrect, because the IFC type definitions differ somewhat for IFC2x3 and IFC4.

ARCHICAD's IFC Translators dialog and the Type Mapping subdialog will alert you about any incompatible Type Mapping definitions, and help you fix them.


Here, you have a custom Type Mapping Preset that is supposed to be compatible with the IFC4 Schema. But the Compatibility panel indicates a problem:




Click the three-dot button to open the Type Mapping Preset dialog. Here, too, the problem is indicated.



Click the **Info** button to find out more. Now the Compatibility Info dialog lists the problematic mapping items (here: Footing, Pile, and Ramp).




Click **OK** to return to the main dialog, then click to open **Map IFC Types for Export** dialog...




In the **Map IFC Types for Export** dialog, set the filter to "Show IFC Entities for IFC4 Schema," as shown in the image below.

This will set up the dialog box so that you are forced to choose mapping definitions compatible with IFC4.




In the left-hand tree view, you can see the Classification items that have errors: they are marked with warning triangles. These items were probably mapped correctly for IFC2x3, but since naming standards have changed or been expanded, you have to re-map these items to use the corresponding new terms for IFC4. This will be easy.


Select the problem Classification item (e.g. Footing).
 Its mapping definitions are on the right. The IFC Type is okay, but the IFC Type Product is missing.



2. Click the IFC Type Product pop-up to see compatible mapping choices. Select one and click Choose.



The mapping issue for the Footing item is solved.




Repeat this re-mapping for each of the problem elements to ensure that your Type Mapping preset is compatible with IFC4.

Geometry Conversion for IFC Export

File > Interoperability > IFC > IFC Translators

Choose a Translator for Export and open the Geometry Conversion preset.



These settings define how to convert the geometry of ARCHICAD elements exported to IFC.

The conversion settings are divided into categories:

Conversion of ARCHICAD Elements

Hierarchical ARCHICAD Elements

IFC Schema-Related Options


Composite Structures and Complex Profiles

Conversion of ARCHICAD Elements

Export only geometries which "Participate in Collision Detection"

Exports only elements whose ARCHICAD Building Material includes the "Participates in Collision Detection" option ON. (This is set at **Options > Element Attributes > Building Materials > Properties**).

Use this option to export composite elements and complex profiles, which don't have solid geometries, as real air gaps. This way, MEP engineers (who receive the ARCHICAD IFC file) can place pipes in the gaps without collision detection; only element parts which have real geometry will participate in collision detection.



Export Bounding Box

Exports the dimensions of the building elements' bounding box.

Export Geometry of IFC Type Products

Assigns a representative geometry to each Type Product. (This option is required for Concept Design BIM 2010.)

Each type (e.g. lfcFurnishingElementType) will use a representative geometry of the elements that belong to it (e.g. lfcFurnishingElement).

Export gross geometry of elements (Export holes separately)

Elements containing Doors, Windows and/or Openings are exported with their gross geometry. For example, a host Wall is exported with its gross geometry, without considering the hole created by a window.


Use this option to ensure accurate cost calculation using the IFC model, where the opening geometry will be considered separately.

Note: Openings are exported by checking IfcOpeningElement in the Model Filter for IFC Export. This is generally checked by default.

If the **Export gross geometry** option is *unchecked*, then elements cannot be created using extrusion. In this case, extruded elements with holes are exported as BREP!

Export all model elements' geometry as:

This describes how the exported element geometry will be interpreted. Choose one of the three options from the pop-up: BREP; Parametric (Extruded/revolved); or Parametric with exceptions. See below.




BREP


- All model elements are exported using BREP (Boundary Representation) geometry, together with their junctions.
- This method is useful in the "reference model" workflow.
- Provides the most exact reproduction of element geometry, together with its specialized sections and junctions.
- Exported elements are transformed into non-editable elements, and their parameters are lost.
- The elements will be exported in the color displayed in the current ARCHICAD view, including colors from Graphic Overrides, Renovation Status, and Issue highlights.

Parametric (Extruded/revolved)


- All model elements are exported using Parametric (Extruded/revolved geometry.)
- This is the format usually supported by static analysis programs, in which element parameters are important, but their special cut angles (such as the slanted edge of a slab) are not important.
- Retains the elements' parameter values (such as thickness, height, location of reference line or edge).
- The skin structure of composite materials cannot be fully preserved because of the IFC standard's limitations.
- Certain specialized sections are not retained.

Note: Morphs, Objects, Shells and certain Walls or Beams with unusual profiles cannot be exported as parametric: these are always exported using BREP.






Parametric with exceptions



- This exports elements as parametric (as described above). However, you can set separate export preferences for **Elements in Solid Element** Operations and **Elements with junctions**:
 - BREP (as described above)
 - Extruded/Revolved (as described above)
 - Extruded/Revolved without junctions: Elements are exported without the priority-based intersections, resulting in a faster export process.
 - Recommended for structural analysis programs, for which the elements' reference lines/surface information is sufficient, and detailed intersections are not required.

Define IFC model position by:

Choose to locate the IFC Site entity using the Survey Point and/or Project Origin.



- Survey Point and Project Origin (default): Used in most coordination workflows.
- **Project Origin only:** Use this if model position is unimportant (e.g. to use the model to create budget calculations). This workflow is most typical in German-speaking markets.
- Survey Point only: Use this only if the model is far from the Project Origin.

Notes:

- The program considers the Survey Point even if it is not visible in the exported view
- To assign geographic property data, use the Survey Point's Georeferencing data. These properties can be shared with any project participants via IFC.

Note on Export of IFC Site Geometry:

As of ARCHICAD 23, all elements that are IFC Site Geometry are exported to IFC as solid bodies.

ARCHICAD elements are IFC Sites if they are:

- · Classified using "IfcSite" as their IFC Type, or
- Saved as Objects having the Subtype "IFC Site"

Mapping IFC Location Data From ARCHICAD and Revit

IFC	ARCHICAD 20 and up	Revit
IFC Global Origin	Survey Point	Survey Point
Position of IfcSite entity	Project Origin	Project Base Point

Hierarchical ARCHICAD Elements

Choose a conversion option for each type of hierarchical element: Curtain Walls, Stairs, Railings.

- Convert to single element: The hierarchical element is exported as a single IFC entity, which contains
 within itself the geometry of all its sub-elements. The hierarchical nature of the original element (e.g. Stair,
 with all its separate sub-components) is thus lost.
- Keep hierarchy: Retain the original element's hierarchical structure, including sub-elements.

See also Exporting Hierarchical Elements from ARCHICAD as IFC Containers.

IFC Schema-Related Options

Material preservation mode (IFC2x3 only)

Use this control to define whether and how to explode complex elements into Building Element Parts. This choice depends on whether you need to retain the material definitions of the components.

Choose one of the following Material preservation modes:

- Never explode elements. Material preservation is not guaranteed.

 This is the default ontion: complex elements (composites and Profiles) are not exploded in
 - This is the default option: complex elements (composites and Profiles) are not exploded, because doing so multiplies the number of Building Element parts in IFC.
- **Explode only when necessary to preserve materials**. The program will explode an element only if that is the only way to preserve its material definition.
- **Explode all elements into parts, preserve materials.** All complex elements are exploded into parts, and material preservation is guaranteed.

Notes:

- These Material preservation options are relevant for IFC2x3 only.
- For IFC4, use the control below: see <u>Split Complex Building Elements into parts</u>.

Composite Structures and Complex Profiles


Split Complex Building Elements into parts

Use this control to split complex elements into Building Element Parts. This option enables you to comply with IFC4 Reference View. Material definitions are not affected by this option (IFC4 retains material definitions irrespective of whether complex elements are split.)

This option enables composite elements and Complex Profiles to be split into so-called "Building Element Parts". With this option, the receiving Structural Engineer will know that a composite Wall includes an air gap component.

If you check the box:

 the tree structure below is editable: you can choose specific element types to be split into parts. (The unchecked element types will not be split up.) If the box is not checked: no complex elements will be split.




Property Mapping for IFC Export


File > Interoperability > IFC > IFC Translators

Choose a Translator for Export and open the Property Mapping preset.

From this preset dialog, click the Map IFC Properties for Export to access the mapping definitions.




These mappings define the IFC properties assigned to elements when exported from ARCHICAD.



Tree list of IFC Entities

IFC Entities are listed in the tree at left.

- · Use the pop-ups if needed to filter the tree list:
 - filter by Schema (IFC2x3 or IFC4)
 - **Note:** A parent entity, if it can be used for property mapping, will be displayed even if it does not belong to the Schema in the current filter
 - filter by domain (Structural or MEP). For example, the Structural domain contains the building element (IfcBuildingElement) types (IfcBeam, IfcColumn, etc.) while the MEP domain contains the IfcDistribution types.
 - filter by IFC Assignment types, IFC Type Objects, or IFC Spatial element types
 (IfcSpatialStructureElements: IfcSite, IfcBuilding, IfcBuildingStorey and IfcSpace).




Filter IFC Entities in Tree List


Note: IFC Entities in parentheses are necessary to the IFC Schema, but have no ARCHICAD elements assigned to them directly.

List of IFC Properties


The IFC Properties of each selected entity are listed in the IFC Properties column.



- Property data assigned to a parent element (such as IfcElement) are automatically assigned to all its child elements (e.g. IfcBeam, IfcColumn, IfcSlab, IfcWall, etc.)
- BOLD TYPE: IFC Entities which have property set data assigned to them are shown in BOLD.
- BLUE TYPE: Properties of a child element are shown in blue type. You can see its parent type name in parentheses.
- Chain icon: Indicates that the property has a mapping rule. View its mapping rule at the right side of the dialog box.
- X: Delete any data item by clicking the red X. Attributes cannot be deleted.



Property assignment can be modified only at the parent level. Thus, to create a common property for all
building elements, you don't have to create it for every single building element type (IfcWall, IfcColumn,
IfcSlab, etc.): instead, create it once at a higher level (e.g. at IfcElement).



A mapping rule can be assigned at different levels. For example, you can apply a rule at the IfcElement level, which will be applicable to all of its child elements (e.g. IfcBeam).

A property's *mapping rule* can be redefined at the child level, too.

Add New Property/Classification Reference

To add a new IFC Property or Classification Reference data to the currently selected entity, do one or both of the following:

• Click the **New** button to create a New Property or Classification.

The same function is available in the IFC Project Manager and Element Settings dialog boxes.

See Create New, Custom IFC Property.

Import from Current Project

Click this to add all the custom IFC Property Sets and Properties of the current project (defined in either IFC Project Manager or Element Settings) to the Property Mapping preset.

Note: If a custom property assigned to an IFC element type (for example IfcWall) is not yet available in the current project, it is not displayed in the IFC management dialogs until one instance of the type has been defined in the model.

Clear All Settings


Delete the entire contents (mapping rules, Properties and Classification References) of the current Property Mapping Preset.

Related Topics

Predefined Property Mapping (Export ARCHICAD to IFC)
Preview Translator

How to create a Mapping Rule

- 1. Select the IFC Property which you would like to map. Data in italic type cannot be mapped.
- 2. Click on the "New Rule" button. The "Empty Rule" field appears.
- 3. from the "Add Content" drop-down button, select a Rule Content type:
 - Parameters & Properties (as the Interactive Element Schedule)
 - Library Part Parameters (as the Interactive Element Schedule)
 - Static Text




- 4. Add fields to the rules. Fields can have types: e.g. "Thickness" is length measure, "Area" is area measure, "Library Part Name" is string. If a rule contains more than one field, the fields are always a concatenation of fields converted to a string. Conversion is based on calculation units (Project Preferences > Calculation Units). Fields implicitly contain filters: for example, the Wall's "Height" field can only be evaluated for Wall elements. "General" fields are listed at tool levels too and are valid only for that specific tool.
- 5. Library Part Parameters can be set in two ways:
 - Library Part dependent: The selected Library Part parameter will be in effect only for elements that contain this parameter. If the Library Part parameter was defined at the Object subtype level, then the parameter mapping will take place for the child elements, too. For example, if we are mapping the "gs_list_cost"variable parameter of the GS Door Object subtype, then the mapping will be in effect for all Doors (and ifcDoors) which are child Library Part elements of the GS Door (such as Door, Double Door, Metal Door, etc.) See examples below.
 - Library Part independent: the parameter variable (e.g. "gs_list_cost") will be in effect for the mapping, regardless of which Library Part it was chosen from. For example, if you select the "gs_list_cost" parameter of the Double Door for mapping as a Library Part Independent parameter, then the mapping will take place for every Door that accesses the "gs_list_cost" parameter. If this door

parameter is used for mapping at the IfcElement level, then it will be mapping for all IFC entities which are child entities of the IfcElement and which include the "gs_list_cost" parameter (such as Furnishing elements, e.g. Armchair and Chair). See examples below.




Notes:

- If the Property Mapping Preset contains a mapping rule involving a Library Part parameter which is not loaded in the project, then the rule, the mapped IFC data, and the mapped IFC Entity data are all shown in red.
- You can assign multiple rules to a single property. This is useful, for example, if several tools will generate the same IFC element type. Rules will be applied in the order in which they appear on the user interface: the first valid rule will be applied.



String-type rules can be split. Separator type, separator position and split type give you several ways
to split a string. For example, use a split to cut out a particular fragment of a Library Part Name.




Related Topic

Examples of Property Mapping Rules

Examples of Property Mapping Rules


Example 1

Map the user-defined "Acoustic Rating" property (Options > Property Manager) to the "AcousticRating" property defined for the IfcWall.




Example 2

Map the "Fire Resistance Rating" parameter of windows to the "FireRating" property defined for the IfcWindow.



Example 3

Define the "Name" Attribute of IfcWall elements using a combination of Wall "ID" and "Building Material/Composite" Name.




Example 4: Mapping Rule by IFC Type Product


You can apply data mapping rules to the IFC data of IFC Type Product elements.

For example, generate the names of Door types (Name Attribute of IfcDoorStyle) from the combination of the Library Part Name, the Width and Height parameters of a Door.

Define the "Name" Attribute for IfcDoorStyle by using a fragment of the Door "Library Part name" + static text "-" + "Width" + static text "X" + "Height".



This rule overwrites the default IfcDoorStyle creation rule (see <u>IFC Type Product</u>) with new IfcDoorStyle names (you can double-check the result in the IFC Project Manager).





Example 5

Define the "Cost" Property for IfcDoor as Library Part dependent parameter.

For mapping, choose the "gs_list_cost" parameter of the "GS Door" Library Part.

To find this parameter, go to the **Add Content** drop-down button and choose **Library Part parameters**. From the appearing dialog box, search for the gs_list_cost parameter as shown:







The mapping rule is valid for the Library Parts which are child elements of the "GS Door" subtype (e.g "Door", "Double Door", "Metal Door", etc.).


Example 6

Define the "Cost" Property for IfcDoor as Library Part independent parameter. For mapping, choose the "gs list cost" parameter of the "Double Door".

To find this parameter, go to the **Add Content** drop-down button and choose **Library Part parameters**. From the appearing dialog box, first select the Double Door library part, then search for the gs_list_cost parameter as shown. However, make sure to add it as a **Library Part Independent** parameter:







Example 7


Define the "Cost" Property for **IfcElement** as Library Part independent parameter. For mapping, choose the "gs_list_cost" parameter of the "Double Door". The mapping rule is valid for not just IfcDoor elements but **all other Library Parts** which will be converted to IFC Entities that are child element of IfcElement (e.g. IfcWindow, IfcFurnishingElement, IfcDistributionElement, IfcTransportElement etc.) and contain the "gs_list_cost" parameter (e.g "Armchair", "Desk", "Basin", "Sink" etc.).

Data Conversion for IFC Export

File > Interoperability > IFC > IFC Translators

Choose a Translator for Export and open the Data Conversion preset.

Use this dialog to define which data, in addition to element geometry, should be exported to IFC. Such data can be useful in data exchange with facility management, energy analysis or cost estimation programs.



Select ARCHICAD Data to Export

Check the boxes of the ARCHICAD Data types you wish to export.

The required data varies depending the purpose of the resulting IFC file (and the software that will be used to open and/or edit it.)

Classifications

ARCHICAD Classifications are exported as IFC Classification Reference data.

Element Properties

Check to export ARCHICAD Properties as IFC Properties. (ARCHICAD Properties are defined in **Options** > **Property Manager**, and assigned to individual elements in their Settings dialog boxes or through the Interactive Schedule.)

Select this list item and use the popup to choose to export All properties, or Visible properties only.



Note: The Visible Properties option is only relevant if you have loaded an Add-On which controls property visibility in ARCHICAD. If no such add-on is loaded, then all properties are exported in every case.

Building Material Properties and Classifications

Check to export ARCHICAD Building Material Properties (defined at Options > Element Attributes > Building Materials) as IFC Properties, and Building Material Classifications as IFC Classification References.

In IFC 2x3: Exported Building Material data is associated to the exported elements.


In IFC4: Exported Building Material data is associated to IFC Materials.

Element Parameters

Check to export ARCHICAD element parameters that convert to IFC Quantities or IFC Properties, depending on their type.

Note: Choosing this option will significantly increase IFC file size. Export parameters only if you know that the target application can read these data.

To filter the exported parameters by type: Select this list item and use the popup to choose to export **All** parameters, or **Quantity-type/Property-type data only**.




- Quantity-type data include e.g. Weight, Length, Area, Volume, Time. Useful for data exchange with programs that can read quantities.
- Property-type data include e.g. Library Part parameters.

Component Parameters

Export parameters of Composite Skins and Complex Profile components as IFC Properties or IFC Quantities, depending on their type.

To filter the exported parameters by type: Select this list item and use the popup to choose to export **All** parameters, or **Quantity-type/Property-type data only.**



- Quantity-type data include e.g. Weight, Length, Area, Volume, Time. Useful for data exchange with programs that can read quantities.
- Property-type data include e.g. Library Part parameters.

As a result, the exported Component data can be interpreted in IFC receiving applications, such as Solibri.

Door-Window Parameters

Export detailed information about ARCHICAD openings as IFC Door-Window Lining or Panel properties.

Zone Categories

Export the Zone Categories data (Code and Name) of ARCHICAD Zones as IFC Space Classification Reference data (ItemReference and Name).

Export IFC Properties

Choose an option for which IFC Properties and Classification References to export:

- All IFC Properties (all which are visible in the IFC Project Manager, no filter on)
- Only Properties set in the Property Mapping Preset for the selected Translator. (These properties are shown in the IFC Project Manager if you turn on the Show Only Properties from Preview Translator filter)

Select Derived Data to Export

Check one or more types of data to export to the IFC model.

• IFC Base Quantities

Check this to export Quantity Takeoff parameters (size, area and volume) to IFC. Useful in cost estimation applications.

The following table summarizes the base quantities by entity types automatically calculated and exported when using this option. The values of IfcSite's base quantities can be set manually at **Info > Project Info** (Site Gross Perimeter and Site Gross Area).


IfcSite	Zone (IfcSpace)	IfcWall	IfcCurtainWall	IfcBeam
GrossArea	Height	Length	Width	Length
GrossPerimeter	FinishCeilingHeight	Height	Length	Width (rectangle profile only)
	FinishFloorHeight	Width	Height	Depth (rectangle profile only)
IfcBuilding	GrossFloorArea	GrossFootprintArea	GrossSideArea	CrossSectionArea
GrossFloorArea	NetFloorArea	NetFootprintArea	NetSideArea	OuterSurfaceArea
	GrossCeilingArea	GrossSideArea		GrossSurfaceArea
Story (IfcBuildingStorey)	NetCeilingArea	NetSideArea	IfcDoor/ IfcWindow/ IfcOpening	TotalSurfaceArea
Height	GrossWallArea	GrossVolume	Height	GrossVolume
NetHeight	NetWallArea	NetVolume	Width	NetVolume
GrossHeight	GrossPerimeter		Area	NetSurfaceArea ExrudedSide
GrossFloorArea	NetPerimeter	IfcSlab	Depth	
	GrossVolume	Width	Volume	IfcColumn/ IfcMember
	NetVolume	Perimeter	Perimeter	Length
	SpaceNetFloorArea BOMA	GrossArea		Width (rectangle profile only)
	SpaceUsableFloor AreaBOMA	NetArea		Depth (rectangle profile only)
		GrossVolume	1	CrossSectionArea
		NetVolume	1	OuterSurfaceArea
			•	TotalSurfaceArea
				GrossVolume
				NetVolume

Export IFC Base Quantities

- **IFC Space Containment:** Export data defining the relationship between ARCHICAD Zones and objects they contain. This feature is useful in facility management applications.
 - Space Containment is relevant only for elements, within an ARCHICAD Zone, which were created using the Object, Lamp, Morph or Slab tools.
 - For Object, Lamp or Morph elements: These elements are in space containment only if their home story is the same as that of the Zone, and if the center of the elements' bounding box falls within the Zone's 2D polygon.
 - A Slab is in space containment if its reference line falls within the Zone top/bottom, and if the Slab polygon falls within the Zone polygon.
 - Click Filter Containment to limit the contents of the Space Containment by their IFC Element Type.


• **IFC Space Boundaries:** Export geometry data of ARCHICAD Zones. (Useful in thermal calculation applications.)

ARCHICAD Zones include precise geometry data that are useful to thermal calculation software applications. Zones are 3D solids in geometrical aspect and in normal cases are bordered by two slabs and four walls. Space boundaries define the logical connection between ARCHICAD Zones (IfcSpace) and the building elements that enclose them. In practice, Walls, Slabs, Roofs, Windows, Doors etc. all have different thermal conductivity properties. If you activate the "IFC Space boundaries" option, ARCHICAD will export Space boundaries and their relations (IfcRelSpaceBoundary) together with the Zones (IfcSpace) to the IFC file. In other words, ARCHICAD will calculate the position, size and adjacency of the elements that border each Zone. ARCHICAD divides the Zone boundaries according to the areas defined and cut by connected elements and openings.



Space Boundaries (defined by Walls):

- 1 Wall part defined by Zone3
- 2 Wall part defined by Zone2
- 3 Wall part cut by connected wall
- 4 and 5 Area defined by door opening



Space Boundaries (defined by Slab):


- 1 Slab part defined by Zone1
- 2 Slab part defined by Zone3
- 3 Slab part defined by Zone2
- 4 Slab part without thermal convection

Unit Conversion for IFC Export

File > Interoperability > IFC > IFC Translators

Choose a Translator for Export and open the Unit Conversion preset.

Set unit types globally for the export of all coordinates, geometric parameters and "Measure"-type IFC Properties.




Filter Model at Import (Secondary Filter)

When Hotlinking, Merging or Opening an IFC file, you must select an IFC Translator for Import, which controls the conversion process. Every IFC Translator for Import has a filtering component (see *Model Filter for IFC Import*), which defines which elements of the IFC model should be placed in ARCHICAD (and which should be skipped).


Each Translator for Import also contains another, secondary Model Filter function. This dialog (Model Filter for Import) allows you to further fine-tune the set of imported IFC elements, based on more specific element categories - e.g. type, story, owner.

However, this secondary Model Filter for Import dialog does not appear by default. To use this feature, turn it on in IFC Translator Settings:


- 1. Open the template file whose IFC translators are being used.
- 2. Go to File > Interoperability > IFC > IFC Translators.
- 3. Select a Translator for Import.
- 4. Under Settings, open Model Filter Settings.



5. Check the Show Model Filter dialog box on import box.



Now the **Model Filter for Import** dialog will appear when you open, hotlink or merge an IFC file to ARCHICAD. Use it to apply custom element filters to the current import process.



Group element list by

To make filtering easier, sort the list items or grouping them as follows:

- IFC Element Type
- Story: List elements by their story location
- Layer: List IFC element types and elements by layer
- Element Owner: List element types and elements according to who created them in IFC

Note on Element Owner

- Elements in IFC models always have an owner attached. If the IFC file is exchanged among many users and programs, an element may have multiple owners.
- The IFCProject entity, like all IFC entities, also has an owner. When an IFC project is imported to ARCHICAD, the IFCProject entity's owner are added to ARCHICAD's Project Info. At export from ARCHICAD, the model elements are all assigned to this owner.

Additional Element Filtering

If needed, filter elements further by IFC Domain or by Structural Function.

Filter Model at Export Working with IFC


Filter Model at Export

Each IFC Translator contains settings for filtering the elements to be exported.

However, you can further fine-tune the set of exported elements during the export process.

IFC Save Options: Elements to Export

- 1. Go to File > Save as.
- 2. Choose an IFC file format.



- 3. In the **Export** field, choose an option:
- Selected elements only in the current view (this option is only available if the current view includes some selected elements)
- Visible elements on all stories. When saving from Floor Plan view, you can choose to export visible
 elements on just the current story. Visibility depends on display settings (Layers, Partial Structure
 display, etc.).
- Entire project, regardless of any selection or layer settings.


Notes:

- In order to export 2D drawing-type elements, annotation element or Grid elements, it is not enough to
 meet the criteria of the filters listed above (e.g. export based on selected or visible elements); you
 must also specifically enable their export, using the translator settings. (See <u>Select 2D Elements to Export</u>.)
- Publisher always uses the 'visible' element export mode, independently of the Model Filter settings of the applied IFC Translator for Export.

Filter Model at Export Working with IFC

IFC Save Options: Model Filter

From the Save dialog, click the **Filter** button to open this dialog box.



Use this list to further filter the elements to be exported.

Group element list by

To make filtering easier, sort the list items or grouping them as follows:

- IFC Element Type
- · Story: List elements by their story location
- · Layer: List IFC element types and elements are listed by layer.
- **Element Owner:** element types and elements are listed according to who created them. (At export, all elements are considered as belonging to the same owner.)

See also Note on Element Owner.

Additional Element Filtering

If needed, filter elements further by IFC Domain or by Structural Function.

Appendix: IFC Terms and Concepts

The following sections provide additional detail about terms and concepts used in IFC.

Model View Definitions


IFC Data Types

Model View Definitions

A *Model View Definition*, MVD (or IFC View Definition) is a recommendation for which data and elements the IFC model should include, depending on the purpose of the model exchange.

Model View Definitions are either defined within buildingSMART International, or by other organizations and interest groups.

ARCHICAD IFC Export and Import supports the following Model View Definitions (choose an MVD in the Translator for Export Settings):




IFC2x3 Schema

- The Coordination View is currently the most widely implemented view of the IFC Schema. Its main
 purpose is to allow sharing of building information models among the disciplines of architecture, structural
 engineering, and building service. It contains definitions of spatial structure, building, and building service
 elements. ARCHICAD is certified for both import and export of the latest version: IFC2x3 Coordination
 View 2.0.
- The IFC2x3 Coordination View (Surface Geometry) is a simplified publishing format (i.e. a subset) of the Coordination View. This format is suitable for viewing (since all IFC viewers support this format), design coordination, clash prevention during design, and clash checking, similarly to IFC4 Reference View. "Coordination View (Surface Geometry)" means that every element will be exported with its BREP (boundary representation) geometry. This method comes closest to reproducing the real shape of the element, together with its specialized sections, connections and solid operations. (However, the element's parameters are lost, and BREP elements from an imported IFC file are transformed into non-editable elements.)
- The IFC2x3 Basic FM Handover View is an extended version of the Coordination View (developed by buildingSMART) that defines the general requirements for design applications to enable the handover of facility management information. The basic scope can be summarized as the space and equipment list for the spatial and technical systems of a facility. Technically, the Basic FM Handover View fulfills the following requirements above and beyond those of the abovementioned Coordination View: ability to assign furnishing and equipment components to spaces (Space Containment, IFC System), to assign

spaces to zones (IFC Zone), to assign a classification to spaces and components (Classification Reference), to assign manufacturer base properties to components (standard and custom IFC Properties), to assign doors and windows to spaces (Space Boundaries), to assign type information for components (IFC Type Product) and to export base quantities for all project components and spatial structures. This MVD is required in various projects defined by buildingSMART and other organizations. An example is the COBie (Construction-Operations Building information exchange), a specification used in the handover of Facility Management information. It is a spreadsheet data format for the delivery of a subset of building model information, rather than geometric model information. ARCHICAD's BIM-quality models and IFC data exchange capabilities produces data output that is easily converted into COBie documentation, with the help of free or commercial conversion programs.

• There are several other Model View Definitions (generally the extended versions of the Coordination view) specified by organizations or development teams outside of buildingSMART International.

IFC4 Schema



The IFC4 Schema further divides the Coordination View into two Model View Definitions:

Note: The IFC4 Schema is not supported by all applications. Use an MVD of the IFC4 Schema only if you are certain that it is supported by the application that will receive IFC data.

- IFC4 Reference View: Suitable for all BIM workflows based on reference models, where the exchange is
 mainly one-directional. Requested modifications of the BIM data, mainly of the shape representation, are
 handled by a change request to the original author.
 - When exporting to IFC4:
 - the relation connections of chained Walls and Beams are omitted
 - Surfaces of Building Materials are omitted
- **IFC4 Design Transfer View:** Provides building information with support for editing of interconnected elements: inserting, deleting, moving, and modifying physical building elements and spaces, within the limited scope of parametric exchange. An example of a target scenario is an architect providing building design information to an engineer for a particular discipline, where geometric modifications may be needed. Note that the Design Transfer View is not meant for round-trip model exchange scenarios.

All Model View Definitions can be extended by definitions which support additional exchange requirements:

- the Quantity Take-off add-on view adds the ability to transmit base quantities for all spatial and building elements
- the Space Boundary add-on view adds building elements to space relationships to support models in thermal and energy analysis
- the 2D Annotation add-on view supports the exchange of additional 2D element representations and annotations of building models

IFC Data Types

This chapter summarizes the main IFC data types available in ARCHICAD.

IFC Entity

IFC Model Hierarchy

IFC Type

IFC Type Product

IFC Container

IFC Attributes

IFC Properties

IFC Classification Reference

IFC Assignments

IFC Entity

In an IFC model, the project information (generated, for example, from an ARCHICAD project) is represented as a set of IFC Entities - such as IFC Type, Attribute, Assignment, Type Product. Each IFC Entity (for example, an IfcWall) includes a fixed number of IFC Attributes, plus any number of additional IFC Properties. Some IFC Entities express characteristics of other entities. Some of these correspond to ARCHICAD attributes. These correspondences are mapped automatically when the IFC model is generated or exported, or when the IFC model is imported.


ARCHICAD Attribute	IFC Entity
Layer	IfcPresentationLayerAssignment
Building Material	IfcMaterial
Surface	IfcSurfaceStyleRendering
Composite	IfcMaterialLayerSet (extruded geometry) or IfcMaterialList (BREP geometry)
Profile	IfcProfileDef

You can set different preferences for converting Layers, Building Materials and Surfaces of imported IFC models: use the conversion settings of Import translators.

See Layer Conversion for IFC Import and Material and Surface Conversion.

IFC Model Hierarchy

An IFC model is composed of IFC Entities built up in a hierarchical order. As shown in the following illustration, each story level (IfcBuildingStorey) has its corresponding story in ARCHICAD.



In ARCHICAD, all elements and objects are linked to a home story. Thus, by default, the IFC model hierarchy lists them under the IfcBuildingStorey of the same name as the elements' home story. However, in IFC Project Manager, elements can be assigned directly to the IfcSite or IfcBuilding. So, for example, neighboring buildings (e.g. defined by the Morph tool) and site context elements (trees, fences, roads, etc.) can be assigned to the site instead of the project building with its story system.

By default, the IFC elements (for example the IfcBuildingElements) and the IfcSpace entities are on the same hierarchy level in an IFC model. However, ARCHICAD Objects and Morphs - regardless of their Classification - can be displayed on and, for IFC export purposes, linked to the ARCHICAD Zone (IfcSpace) that contains them, instead of to their home story.

IFC Spatial Elements

IFC Spatial Elements are **IfcProject**, **IfcSite**, **IfcBuilding**, **IfcBuildingStorey**, as well as **IfcSpace**. They are at the top of the IFC Project Manager Hierarchy.

These elements can only be managed through the IFC Project Manager, where you can also edit their IFC-related data.

The IFC Attribute values of these spatial elements, however, are derived from the data of the current ARCHICAD project.

IfcSite is the geographic position of the IfcProject. It can have a geometry, but a geometry is not required. In ARCHICAD, site geometry is represented by Mesh elements, Site-type Objects, or elements with "Site Geometry" Classification.

ARCHICAD can handle and import one building (**IfcBuilding**) only. But it can import more than one IfcSite, even though the IfcSite is above the IfcBuilding in the hierarchy. Thus, when importing an IFC file that contains multiple buildings, you can choose only one to import.

See Building and Site Selection.


However, other applications can export a building's topography into multiple IfcSites. In this case, importing the IfcBuilding will import all of the IfcSites, merged into the one IfcSite that actually contains the imported IfcBuilding. As a result, you will end up with a single IfcSite and a single IfcBuilding, but the IfcSite includes all of the IfcSites.

How to Control Global ID (IFC Attribute) Based on ARCHICAD Project Info

By default, ARCHICAD assigns identical GlobalID attributes to the following entities: IFC Project, IFC Site, IFC Building, and IFC Story. More precisely: the Global IDs will be identical, provided that the respective ID fields, defined at ARCHICAD's Project Info dialog box (File > Info) contain identical keywords (or no value at all). However, you can alter these keywords in the Project Info dialog box to control whether the spatial entities have identical or different GlobalIDs.

Suppose you have two separate buildings (stored in two different ARCHICAD projects). You want both projects and both sites to share the same GlobalID; yet you want the various buildings on each site to have different GlobalIDs.

To achieve this, enter the same keyword in the "Project ID" and "Site ID" fields of both projects. Enter different keywords for the "Building ID" fields.



IFC Story entities have no corresponding ID field in the Project Info dialog box. The GlobalIDs of IFC Story entities are derived from their Building ID. If two buildings in two different ARCHICAD projects have the same Building ID, then all stories of those buildings which have the same Story Number will have the same Global ID.


IFC Type

IFC Type is one kind of IFC entity - it groups IFC model elements into a hierarchical structure, represented by the tree structure in the IFC Project Manager.

When a model is exported to IFC format, every one of its elements is assigned an IFC Type. In ARCHICAD, IFC Types are generated based on the Type Mapping definition (either by Tool or by Classification) in the Translator for Export.

See <u>Type Mapping for IFC Export</u>.

in ARCHICAD, view any element's IFC Type in the Manage IFC Properties window of Element Settings (or for any selected element in IFC Project Manager).



You can also use Find & Select to filter the project by "IFC Type" criteria, or use Interactive Element Schedule to list this data for ARCHICAD elements. For example, you can select or list just the model elements having IfcSlab IFC Type.

See Define Element Criteria using IFC Data.

IFC Type Product

An IFC Type Product defines a particular style/type of other entities by relating to them with common IFC Attributes and Properties. For example, IfcWindowStyle is an IFC Type Product, to which many windows (IfcWindow) refer.

IFC Type Product entities are generated for ARCHICAD elements based on the Type Mapping definition in the Translator for Export.

See Type Mapping for IFC Export.

IFC Container

IFC Container (relating object of IfcRelAggregates) is an IFC entity that does not have its own body geometry, but its components (related objects of IfcRelAggregates) contain all geometry and structure-related data.

Exporting Hierarchical Elements from ARCHICAD as IFC Containers

In an ARCHICAD project, the IFC Translator for Export gives you the option of exporting hierarchical elements (Curtain Wall, Stair, Railing) to IFC as either a single element, or as a hierarchical one.

- If exported with the hierarchical method ("Keep Hierarchy"), it will be an **IFC Container** entity, and its subelements will be individual IFC elements. This reflects the multi-part hierarchy of the original ARCHICAD element (e.g. Stair).
- If exported as a single element, it will be a **single IFC entity**, which contains within itself the geometry of all its sub-elements. The hierarchical nature of the original element (e.g. Stair, with all its separate sub-components) is thus lost.
- IFC export that uses the "Explode Composite and Complex Profile elements into parts" option generates IFC Container elements from building elements in the output IFC file: for example a composite wall element is saved as an "IfcWall"-type IFC Container element without geometry, and its skin parts will provide the geometry as "IfcBuildingElementPart" elements.

These export options are found at Geometry Conversion for IFC Export.


IFC Attributes

IFC Attributes are the main identifiers of IFC Entities. The names of IFC Attributes are fixed, having been defined by buildingSMART as part of the IFC standard code.

Most of these IFC Attribute names are derived from the project. For example, the IFC Attributes of an IfcWall building element:

- Globalld: the Globally Unique Identifier of the IfcWall in the IFC model (not editable).
- OwnerHistory: the assignment of the information about the current ownership of the IfcWall.
- Name: its factory-default derived value is IfcWall's ARCHICAD ID (Wall Settings dialog box > Classification and Properties panel).
- Description: an optional textual description.
- ObjectType: an optional text to define a subtype of an element or add type information to it.

Tag: its factory-default derived value is the IfcWall's ARCHICAD "Unique ID" (not the same as IFC Globalld).



OwnerHistory is directly attached to all independent objects, relationships and properties. Its components
and values are derived from project data and hidden in the ARCHICAD user interface. It includes, for
example, the owning actor (OwningUser) (certain owner data is added to ARCHICAD's Project Info (File >
Info).

IFC Properties

IFC Properties are additional (mostly IFC Type-specific) parameters assigned to an IFC Entity. IFC Properties can be standard or non-standard.

- Standard, so-called "IFC2x3 Schema" data are defined by buildingSMART and stored in property sets whose names begin with the prefix "Pset_"
- Non-standard data are created by the exporting application using any property name and stored in any
 property set (the names of these property sets usually contain the name of the exporting application, or
 the IFC Model View Definition which requires the property.

See Property Mapping for IFC Export.

IFC Classification Reference

A Classification Reference (IfcClassificationReference) arranges IFC elements into a category. You can assign an Item Reference identifier, a classification Name attribute and some other optional parameters to all project elements (such as the building, the stories, the building elements, or the zones).

You can classify elements with this system both in IFC Project Manager and the element Settings dialog.

See Create New, Custom IFC Property.

IFC Assignments


IFC Assignments (IfcRelAssigns) define the relationship among project elements. Each assignment type can have its own IFC Attribute (the most significant is the Object Type), and standard and custom IFC Properties. The major assignment types of the IFC standard are the following:

- **IFC Group** (IfcGroup): Use this to group any project elements (building element, story etc.) together. For example: the column and beam components of a frame standing are grouped together. Grouping by multilevel-hierarchy is also available: for example, you can group the frame standing groups in a 'frame-system' group.
- IFC Zone (IfcZone): Use this to group IfcSpace elements (the equivalent of ARCHICAD Zones) together. For example: ARCHICAD Zones having the identical function are grouped into an IfcZone named e.g. "Security Zone." Grouping by multilevel-hierarchy is also available for IfcZone assignments. For example, you can group some ARCHICAD Zones (IfcSpaces) in an IfcZone (Security Zones) that is a part of a higher level IfcZone group (Governmental Zones).
- IFC System (IfcSystem): Use this to group any project elements (especially MEP elements) in a system hierarchy manually, by using MEP Modeler defined systems, or by importing systems exported from e.g. MEP applications. Definition of sub-system hierarchy (parent and child system) is also available. For example: group elevators in a vertical circulation system which can be a child system of a mechanical system. Or, assign plumbing elements to the cold water sub-system of a plumbing system. You can also tie systems to a spacial structure relation (IfcSite, IfcBuilding, IfcStorey or IfcSpace). For example, add to a duct system all the ARCHICAD Zones (IfcSpace) that it runs through.
- · IFC Building Systems
- IFC Distribution Systems

ARCHICAD supports all of the above mentioned IFC Assignment types:

- the IFC Project Manager interface lets you define any assignments in your project and manage all their IFC data;
- all of the above mentioned assignment data are created at IFC model import (for example IfcSystems stored in an MEP-type IFC model, IfcZones defined in an FM application);
- all available IFC Assignments (defined manually or previously imported) are exported with a new IFC model mapped from the current ARCHICAD project.

See Using Assignments in IFC Project Manager.



Appendix: IFC Data Mapping in ARCHICAD

This section contains two charts with detailed mapping information that is built in to ARCHICAD.

Predefined Property Mapping (Export ARCHICAD to IFC)
Built-in IFC Type Mapping for ARCHICAD

Related Topic:

Data Types for Properties in IFC and ARCHICAD


Predefined Property Mapping (Export ARCHICAD to IFC)

The Property Mapping preset of the IFC Translator for Export defines the assignment of IFC Properties and Attributes when exporting ARCHICAD model to IFC.

See Property Mapping for IFC Export.

Some Attribute and Property data come with a predefined mapping rule, which you do not have to create yourself in Property Mapping.

Although these rules do not appear in the Map IFC Properties for Export dialog box, they can be seen (if they have values) with a gray chain icon in the **IFC Project Manager** and Element Settings.



These rules are listed in the following table.

ARCHICAD Command	ARCHICAD Parameter	IFC Entity Types	IFC Data	IFC Project Manager
Project Info	Project Name	IfcProject	Attribute>Name	visible/editable
Project Info	Project Description	IfcProject	Attribute>Description	visible/editable
Project Info	Project ID	IfcProject	Attribute>GlobalId (see How to Control Global ID (IFC Attribute) Based on	-
			ARCHICAD Project Info)	
Project Info	Project Status	IfcProject	Attribute>Phase	visible/editable
Location Set- tings	Project North	IfcProject	Attribute>Representa- tionContext>TrueNorth	-
Location Set- tings	Latitude	IfcSite	Attribute>RefLatitude	visible
Location Set- tings	Longitude	IfcSite	Attribute>RefLongitude	visible
Location Set- tings	Altitude	IfcSite	Attribute>RefAltitude	visible
Project Info	Site Name	IfcSite	Attribute>Name	visible/editable
Project Info	Site ID	IfcSite	Attribute>Global Id (see How to Control Global ID (IFC Attribute) Based on ARCHICAD Project Info)	-

ARCHICAD Command	ARCHICAD Parameter	IFC Entity Types	IFC Data	IFC Project Manager
Project Info	Site Description	IfcSite	Attribute>Description	visible/editable
Project Info	Site Full Address>Site Address1	IfcSite	Attribute>SiteAd-dress>AddressLines	-
Project Info	Site Full Address>Site Address2			
Project Info	Site Full Address>Site Address3			
Project Info	Site Full Address>Site Postal Box	IfcSite	Attribute>SiteAd-dress>PostalBox	-
Project Info	Site Full Address>Site City	IfcSite	Attribute>SiteAd-dress>Town	-
Project Info	Site Full Address>Site State	IfcSite	Attribute>SiteAd-dress>Region	-
Project Info	Site Full Address>Site Postcode	IfcSite	Attribute>SiteAd-dress>PostalCode	-
Project Info	Site Full Address>Site Country	IfcSite	Attribute>SiteAd-dress>Country	-
Project Info	Site Gross Perimeter	IfcSite	BaseQuantity>GrossPerim- eter	-
Project Info	Site Gross Area	IfcSite	BaseQuantity>GrossLan-dArea	-
Project Info	Building Name	IfcBuilding	Attribute>Name	visible/editable
Project Info	Building Description	IfcBuilding	Attribute>Description	visible/editable
Project Info	Building ID	IfcBuilding & IfcBuildingStorey	Attribute>GlobalId (see How to Control Global ID (IFC Attribute) Based on ARCHICAD Project Info)	
Project Info	Contact Full Name>Contact Prefix Title	IfcPerson	Attribute>PrefixTitles	-
Project Info	Contact Full Name>Contact Given Name	IfcPerson	Attribute>GivenName	-
Project Info	Contact Full Name>Contact Middle Name	IfcPerson	Attribute>MiddleNames	-
Project Info	Contact Full Name>Contact Family Name	IfcPerson	Attribute>FamilyName	-
Project Info	Contact Full Name>Contact Suffix Title	IfcPerson	Attribute>SuffixTitles	-
Project Info	Contact ID	IfcPerson	Attribute>Id	-
Project Info	Contact Role	IfcPerson	Attribute>Roles	-
Project Info	Contact Department	IfcPerson	Addresses>Postal>Inter- nalLocation	-

ARCHICAD Command	ARCHICAD Parameter	IFC Entity Types	IFC Data	IFC Project Manager
Project Info	Contact Company	IfcOrganization	Attribute>Name	-
Project Info	Contact Company Code	IfcOrganization	Attribute>Id	-
Project Info Project Info	Contact Full Address>Contact Address1 Contact Full Address>Contact Address>Contact	IfcPerson & IfcOrganization	Attri- bute>Addresses>Postal>Ad dressLines	-
Project Info	Contact Full Address>Contact Address3			
Project Info	Contact Full Address>Contact Postal Box	IfcPerson & IfcOrganization	Attri- bute>Addresses>Postal>Po stalBox	-
Project Info	Contact Full Address>Contact City	IfcPerson & IfcOrganization	Attri- bute>Addresses>Postal>To wn	-
Project Info	Contact Full Address>Contact State	IfcPerson & IfcOrganization	Attri- bute>Addresses>Postal>Re gion	-
Project Info	Contact Full Address>Contact Post- code	IfcPerson & IfcOrganization	Attri- bute>Addresses>Postal>Po stalCode	-
Project Info	Contact Full Address>Contact Country	IfcPerson & IfcOrganization	Attri- bute>Addresses>Postal>Co untry	-
Project Info	Contact E-mail	IfcPerson & IfcOrganization	Attri- bute>Addresses>Tele- com>ElectronicMailAddres s	-
Project Info	Contact Phone Number	IfcPerson & IfcOrganization	Attri- bute>Addresses>Tele- com>TelephoneNumbers	-
Project Info	Contact Fax	IfcPerson & IfcOrganization	Attri- bute>Addresses>Tele- com>FacsimileNumbers	-
Project Info	Contact Web	IfcPerson & IfcOrganization	Attri- bute>Addresses>Tele- com>WWWHomePageURL	-
Story Settings	Elevation	IfcBuildingStorey	Attribute>Elevation	visible/editable
Zone Settings	Name	IfcSpace	Attribute>LongName	visible/editable
Zone Settings	Number (No)	IfcSpace	Attribute>Name	visible/editable

ARCHICAD Command	ARCHICAD Parameter	IFC Entity Types	IFC Data	IFC Project Manager
(element)>Set- tings	Classification and Properties>ID	(IFC element type)	Attribute>Name	visible/editable
(element)>Set- tings	Classification and Properties>Classification	(IFC element type)	Attribute>ObjectType	visible/(editable in Export Trans- lator, Type Map-
(element)>Set- tings	Classification and Properties>Classification	(IFC element type)	Attribute>PredefinedType	ping) visible/(editable in Export Trans- lator, Type Map- ping)
(element)>Set-	Classification and Proper-	(IFC element	PsetCommon>LoadBear-	visible
tings	ties>Structural Function	type)	ing	
(element)>Set-	Classification and Proper-	(IFC element	PsetCommon>IsExter-	visible
tings	ties>Position	type)	nal	
(element)>Set-	Classification and Proper-	(IFC element	AC_Pset_RenovationAnd-	visible
tings	ties>Renovation Status	type)	Phasing>Renovation Sta- tus	
(element)>Set- tings	Classification and Properties>Classification	(IFC type product)	Attribute>ElementType	visible/(editable in Export Trans- lator, Type Map- ping)
(element)>Set- tings	Classification and Properties>Classification	(IFC type prod- uct)	Attribute>PredefinedType	visible/(editable in Export Trans- lator, Type Map- ping)
Schedule>(ele- ment)	General>Unique ID	(IFC element type)	Attribute>Tag	visible/editable
Window/Door Settings	Preview and Position-ing>Width	IfcWindow / Ifc- Door	Attribute>OveralWidth	visible
Window/Door Settings	Preview and Position- ing>Height	IfcWindow / Ifc- Door	Attribute>OverallHeight	visible
(automatic type naming rule)	Bldg Mat/Profile name, element dimensions. For multi-segment: Number of segments, maximum segment	IfcColumn	Pset_ColumnCommon>Reference	visible/editable
	dimensions, segment lengths.			

ARCHICAD Command	ARCHICAD Parameter	IFC Entity Types	IFC Data	IFC Project Manager
(automatic type naming rule)	Bldg Mat/Profile name, element dimensions. For multi-segment: Number of segments, maximum segment dimensions, segment lengths.	IfcBeam	Pset_BeamCommon>Reference	visible/editable

Built-in IFC Type Mapping for ARCHICAD

When an ARCHICAD model is exported to IFC, each element is assigned an IFC Element Type.

Type Mapping is defined in the IFC Translator for Export, in the Type Mapping preset: either by Element Type or by Classification.

See Type Mapping for IFC Export.

The following 3 charts show the Type Mapping that results using the automatic, "by Element Type" method.

ARCHICAD Tool LibPart (By Unld) MEP (By Tool)

ARCHICAD Tool

ARCHICAD Tool	IFCObjectType	IFCObject	IFCObject PredefinedType	IFCTypeObject Predefined- Type
Beam	IFCBeam		IFCBeamType	
Column	IFCColumn		IFCColumnType	
Wall	IFCWall		IFCWallType	
Shell	IFCSlab	ROOF	IFCSlabType	ROOF
Roof	IFCSlab	ROOF	IFCSlabType	ROOF
Slab	IFCSlab	FLOOR	IFCSlabType	FLOOR
Mesh	IFCSite			
Morph	IFCBuildingElementProxy		IFCBuildingElement- ProxyType	
Railing	IFCRailing		IFCRailingType	
Baluster	IFCMember		IFCMemberType	
Handrail	IFCMember		IFCMemberType	
Inner Post	IFCMember		IFCMemberType	
Railing Panel	IFCMember		IFCMemberType	
Railing Post	IFCMember		IFCMemberType	
Rail	IFCMember		IFCMemberType	
Toprail	IFCMember		IFCMemberType	
Handrail Connection	IFCMember		IFCMemberType	
Rail Connection	IFCMember		IFCMemberType	
Toprail Connection	IFCMember		IFCMemberType	
Handrail End	IFCMember		IFCMemberType	
Rail End	IFCMember		IFCMemberType	
Toprail End	IFCMember		IFCMemberType	
Railing Node	IFCMember		IFCMemberType	
Railing Segment	IFCMember		IFCMemberType	
Railing Pattern	IFCMember		IFCMemberType	
Stair	IFCStair		IFCStairType	
Riser	IFCMember		IFCMemberType	
Stair Structure	IFCMember		IFCMemberType	
Tread	IFCMember		IFCMemberType	
Curtain Wall	IFCCurtainWall		IFCCurtainWallType	
Curtain Wall Frame	IFCMember		IFCMemberType	
Curtain Wall Panel	IFCPlate		IFCPlateType	
Curtain Wall Accessory	IFCDiscreteAccessory		IFCDiscreteAccessory- Type	

ARCHICAD Tool	IFCObjectType	IFCObject	IFCObject PredefinedType	IFCTypeObject Predefined- Type
Curtain Wall Seg-	IFCDiscreteAccessory		IFCDiscreteAccessory-	
ment			Туре	
Curtain Wall Junction	IFCDiscreteAccessory		IFCDiscreteAccessory- Type	
Zone	IFCSpace		IFCSpaceType	
Door	IFCDoor		IFCDoorType	
Skylight	IFCWindow		IFCWindowType	
Window	IFCWindow		IFCWindowType	
Opening	IFCOpeningElement			
Object	IFCFurniture		IFCFurnitureType	
Lamp	IFCLightFixture		IFCLightFixtureType	
Fill	IFCAnnotation		Undefined	
Line	IFCAnnotation		Undefined	
Spline	IFCAnnotation		Undefined	
Polyline	IFCAnnotation		Undefined	
Circle	IFCAnnotation		Undefined	
Arc	IFCAnnotation		Undefined	
Dimension	IFCAnnotation		Undefined	
Angle Dimension	IFCAnnotation		Undefined	
Level Dimension	IFCAnnotation		Undefined	
Radial Dimension	IFCAnnotation		Undefined	
Text	IFCAnnotation		Undefined	
Label	IFCAnnotation		Undefined	

LibPart (By Unld)

LibPart (By Unld)		
ARCHICAD	IFCObjectType	IFCTypeObjectType
curtainWallFrame	IFCBuildingElementProxy	IFCBuildingElementProxyType
curtainWallPanel	IFCBuildingElementProxy	IFCBuildingElementProxyType
stair	IFCStair	IFCSpatialStructureElementType
opening	IFCOpeningElement	IFCMemberType
wallOpening	IFCOpeningElement	IFCMemberType
wallDoor	IFCDoor	IFCDoorStyle
wallWindow	IFCWindow	IFCRampFlightType
roofOpening	IFCWindow	IFCRampFlightType
beam	IFCBeam	IFCBeamType
column	IFCColumn	IFCColumnType
covering	IFCCovering	IFCCoveringType
light	IFCFlowTerminal	IFCFlowTerminalType
curtainWall	IFCCurtainWall	IFCCurtainWallType
discreteAccessory	IFCDiscreteAccessory	IFCDiscreteAccessoryType
footing	IFCFooting	IFCFlowTreatmentDeviceType
furnishing	IFCFurnishingElement	IFCFurnishingElementType
railing	IFCRailing	IFCRailingType
ramp	IFCRamp	IFCRailingType
roof	IFCRoof	IFCRampFlightType
slab	IFCSlab	IFCSlabType
wall	IFCWall	IFCRampFlightType
wallEnd	IFCCovering	IFCCoveringType
gridElementMarker	IFCGridAxis	IFCFurnishingElementType
slabOpening	Undefined	IFCWindowStyle
transport	IFCTransportElement	IFCRampFlightType
buildingElementProxy	IFCBuildingElementProxy	IFCBuildingElementProxyType
ifcMechanicalFastener	IFCMechanicalFastener	IFCMechanicalFastenerType
ifcFastener	IFCFastener	IFCFastenerType
ifcExtruded	IFCBuildingElementProxy	IFCBuildingElementProxyType
ifcBeamExtruded	IFCBeam	IFCBeamType
ifcColumnExtruded	IFCColumn	IFCColumnType
ifcDiscreteAccessoryEx-	IFCDiscreteAccessory	IFCDiscreteAccessoryType
truded		
ifcFootingExtruded	IFCFooting	IFCFlowTreatmentDeviceType
ifcOpeningExtruded	IFCOpeningElement	IFCMemberType

MEP (By Tool)

MEP (By Tool)				
ARCHICAD	IFCObjectType	IFCTypeObjectType	IFCTypeObject PredefinedType	
CableCarrierBend	IFCCableCarrierFit-	IFCCableCarrierFit-	BEND	
	ting	tingType		
CableCarrierRigidSeg-	IFCCableCarrierSeg-	IFCCableCarrierSeg-	NOTDEFINED	
ment	ment	mentType		
CableCarrierTee	IFCCableCarrierFit-	IFCCableCarrierFit-	TEE	
	ting	tingType		
CableCarrierTransi-	IFCCableCarrierFit-	IFCCableCarrierFit-	REDUCER	
tion	ting	tingType		
CableCarrierWye	IFCCableCarrierFit-	IFCCableCarrierFit-	TEE	
	ting	tingType		
DuctBend	IFCDuctFitting	IFCDuctFittingType	BEND	
DuctEndCap	IFCDuctFitting	IFCDuctFittingType	EXIT or ENTRY	
DuctFlexibleSegment	IFCDuctSegment	IFCDuctSegmentType	FLEXIBLESEGMENT	
DuctObstruction	IFCDuctFitting	IFCDuctFittingType	OBSTRUCTION	
DuctOffset	IFCDuctFitting	IFCDuctFittingType	TRANSITION	
DuctRigidSegment	IFCDuctSegment	IFCDuctSegmentType	RIGIDSEGMENT	
DuctTakeOff	IFCDuctFitting	IFCDuctFittingType	JUNCTION	
DuctTee	IFCDuctFitting	IFCDuctFittingType	JUNCTION	
DuctTransition	IFCDuctFitting	IFCDuctFittingType	TRANSITION	
DuctVerticalObstruc-	IFCDuctFitting	IFCDuctFittingType	OBSTRUCTION	
tion				
DuctWye	IFCDuctFitting	IFCDuctFittingType	JUNCTION	
PipeBend	IFCPipeFitting	IFCPipeFittingType	BEND	
PipeCombinationWye	IFCPipeFitting	IFCPipeFittingType	JUNCTION	
PipeInlineFlowDevice	IFCPipeFitting	<ifc_subtype parame-<="" td=""><td><ifc_predefinedtype< td=""></ifc_predefinedtype<></td></ifc_subtype>	<ifc_predefinedtype< td=""></ifc_predefinedtype<>	
		ter>	parameter>	
PipeInlineFlowDevice	IFCPipeFitting	<ifc_subtype parame-<="" td=""><td><ifc_predefinedtype< td=""></ifc_predefinedtype<></td></ifc_subtype>	<ifc_predefinedtype< td=""></ifc_predefinedtype<>	
		ter>	parameter>	
PipeRigidSegment	IFCPipeSegment	IFCPipeSegmentType	RIGIDSEGMENT	
PipeSanitaryTee	IFCPipeFitting	IFCPipeFittingType	JUNCTION	
PipeTakeOff	IFCPipeFitting	IFCPipeFittingType	JUNCTION	
PipeTee	IFCPipeFitting	IFCPipeFittingType	JUNCTION	
PipeTransition	IFCPipeFitting	IFCPipeFittingType	TRANSITION	
PipeWye	IFCPipeFitting	IFCPipeFittingType	JUNCTION	

Data Types for Properties in IFC and ARCHICAD

IFC Data Type	ARCHICAD Data Type	Description
Single String	String	Any text or number
Single Real	Number	Any number expressed in decimals
Single Integer	Integer	A whole number
Single Boolean	True/False	A logical true or false value
List String	Tags List	A tag or series of tags.
Enumerated String	Option Set	Provides a fixed set of options. The user can choose a value from this set.